

# Merit LILIN Application Note for Interoperable test of Synology Software and LILIN IP Cameras

Document Number : A00012 Date : 09/21/2012 Dept : Technical Support, Taipei

Subject: Interoperable test of Synology Software and LILIN IP Cameras

LILIN IP camera platform: 2MP & 3MP IP cameras LILIN IP camera firmware: version: 1.0.488 or above Synology software:V6.0-2337

### Step 1:

Select the "Menu" button on the top left of the screen and press "Surveillance Station".



**Step 2:** Select "Camera List→Add→Add Camera".

Live View	Timeline	Management				🤤 Surveillan	ce Station 6 🛛 👤
Camera	Add Delete	Edit a Enable a	Refresh Configura	tion Advanced			
🧕 Camera List	Add Camera	Name	IP address	Status	Occupied	Limit to	Rotation
ng Camera Group	Add Batch						
Event							
🗎 Event List							
🛃 Export							
🚱 Mount							
System							
\varTheta Е-Мар							
Outification							
🗱 Advanced							
🔒 Privilege							
🔎 License							
😭 Log							
	K K Page 1	of1 > > C					No data

# **Step 3:** Select "Quick Setup".

Add	Camera				? X
	Setup				
	Select a setup mode:	Quick Setup			
		Complete Setup			
			Previous	Next	Cancel

## Step 4:

Type the "Name, IP address, port, Brand, username and password", and press Finish.

d Camera						? X
Device Info						
Name: IP address: Port: Brand: Camera model: Username: Password:	IPG1032 192.168.3.5 80 [ONVIF] Generic_ONVIF admin ••••	ρ ~ ~			]1	
			F	Previous	Finish	Cancel

**Step 5:** The camera is successfully added as shown below and now press the Live View button.

	Live View	Timeline	Management					🍳 Surveillance Station 6 🔒 👤		
Cam	era	Add 🖌 Delete	Edit 4 Enable 4	Refresh Configurat	ion a Advanced a					
0	Camera List	Preview	Name	IP address	Status	Occupied	Limit to	Rotation		
<b>1</b> 0	Camera Group		IPG1032	192.168.3.5	Normal	0 (GB)	10 (GB) / (days)	Yes		
Even	t									
	Event List									
B	Export									
0	Mount									
Syste	em									
0	Е-Мар									
	Notification									
*	Advanced									
	Privilege									
۹	License									
È	Log									

# **Step 6:** Select the configure button to set up the layout of the camera.

Live View	Timeline	Management		🔤 Surveillance Station 6 🛛 👤
default	nfigure		Deleted	
Liveview Analytics Toggle Analytics History				
Patrol _				
EN 25 1 20 15				

## Step 7:

Drag and drop the camera "IPG1032" to the right side and press "Save" button.

Layo	ut Management										? X
	+ -	Name:	default				✓ Set a	is default			
	default	E-Map:	[None]				Fix a	spect rati	0		
	2	-									
								36	49 (	-	
											-
		🕨 🚔 All C	ameras		IPG1022	(Camera d	eleted)				
		🧕 IP	PG1032								
											10
								Custo	mize	Preview	
		*Press and h	old the "Shift" o	or "Ctrl" key for n	nultiple sele	ection.					
										Close	e Î

## Step 8: After all the above steps are done and the camera's live view is shown below.

