







Tollon wired siren & strobe light

			
Wired Siren & Strobe light	SL-100	SL-150	SL-150B
Rated power	15W	15W	15w
Rated current(A)	160mA	120mA	160mA
Rated voltage(V DC)	12 VDC	12V/24V DC	DC12/24V
Operating Voltage Range(V DC)	6-15 VDC	6-15VDC	DC6-15VDC/3-28V
Frequency		120	2.3-4.3KHz
Flashes/minute	105±3	105±3	120
SPL Db/1M	105dB	105DB	105DB
Tone	Wavine	105DB	Sound 1/8 Tone
Note	N/A	Lighting Halogen Bulbs	
Color	Len Color: Red, Blue, Orange	Red, Blue, Yellow/White	Red, Blue, Yellow/White





Tollon wired outdoor /indoor siren strobe light

			
Siren & Strobe light	SL-200	SL-200B	HC-P110
Power	15w	15W	15w, 2.3-4.3KHz
Siren current(A)			
Strobe current(A)			
Siren voltage			
Strobe voltage			
Rated current(A)	300mA		120mA
Rated voltage(V DC)	12V/24V DC	12V/24V DC	DC12/24V
Operating Voltage Range(V DC)			DC6-15VDC/3-28V
Flashes/minute	120	105±3	120
SPL Db/1M	105DB	105DB	105DB
Material	Lighting-Halogen Bulbs	ABS	1/8 Tone
Note			
Color	Len color: Red, Blue	white	White/red

Tollon wired outdoor /indoor siren strobe light

			
Siren & Strobe light	SL-350	SL-400	SL-450
Power	15W	15W	15W
Siren current(A)			
Strobe current(A)			
Siren voltage			
Strobe voltage			
Rated current(A)			
Rated voltage(V DC)	12VDC	12VDC	DC12-14V
Operating Voltage Range(V DC)	6-15VDC		DC12V
Flashes/minute	110±3	120±3	
Material			ABS
SPL Db/1M	110±3	120±3	105±3
Tone			1/8 Tone
Optional			2V, 1.3A/Rechargeable
Note			2 way tamper switch protection len colors is red/blue/orange/white
Color	Red, blue, orange		White/Red

Tollon wired outdoor siren strobe light

			
Siren & Strobe light	SL-550	SL-650	SL-700
Power	15W	50w	20W(peak)
Siren current(A)	400mA	1200mA	500mA
Strobe current(A)	100mA	250mA	100mA
Siren voltage	DC 16-14V	DC 24V	DC16-14V
Strobe voltage	DC 12V	DC 24V	DC 12V
Rated current(A)			
Rated voltage(V DC)	100-120Minute	120-150minute	100-115±3
Operating Voltage Range(V DC)			DC14V/24V
Flashes/minute			DC3-28V
Siren frequency			120-150±3minute
SPL Db/1M	115±3	108±3	132,4 kHz
Material	Material ABS/AS/PC	ABS/AS/PC	ABS
Tone			1.2/2B
Optional			ABS/AS/PC
Note	strobe len pc lens(blue or red)	Blue/Red/Orange	light LED or tube red/orange/blue
Color			strobe: red/orange/blue

Tollon Wired strobe light

			
Strobe light	SL-800	SL-01	SL-02
Rated current(A)			
Rated voltage(V DC)	DC3-15V	DC6-12V	DC12/24V
Operating Voltage Range(V DC)			DC12/24V
Strobe Current(A)			1500mA(Average)
Flashes/minute	65	100	
SPL Db/1M	115±3		
Material	Material	light source: tube or leds	ABS/AS/PC
Optional		Red/Blue /Amber	Light Source: Tube/Leds
Color	LEN Colors: Red, Orange, Blue	Blue/Red/Yellow	Red/Blue/Orange

Tollon Wireless siren strobe light

	
Siren & Strobe light	SL-350W(Wireless)
Power	DC12V 400mA
Siren current(A)	5230mA
Strobe current(A)	
Siren voltage	
Strobe voltage	
Rated current(A)	433/315MHz
Rated voltage(V DC)	
Operating Voltage Range(V DC)	868/433/315MHz(20 wireless zones)
Flashes/minute	
SPL Db/1M	
Material	
Optional	Backup battery AAA 7.2V
Color	7.4V400mA, Rechargeable lithium battery


Fire siren with light

			
Strobe light	FA-411 /FA-411L	FA-410/FA-410L	FA-416
Rated current(A)	100mA	140mA	140
Rated voltage(V DC)	24V DC	24V DC	12VDC
Operating Voltage Range(V DC)	DC6-15V	15-30V DC	DC6-12V
Strobe Current(A)			
Flashes/minute	FLASH INTENSITY ≥ 1.2WS,FLASH PERIOD ≥ 1.5S	Light Life: 30000 flashes	80
SPL Db/1M	115±3	80±3	100±3
Material		Polycarbonate	Polycarbonate
Optional		Light source: tube or leds	Light Source: Tube/Leds
Color	LEN Colors: Red, Orange, Blue	Red/Blue /Amber	Red

Fire siren with light

			
Strobe light	FA-412	FA-413	FA-418
Rated current(A)			
Rated voltage(V DC)	DC3-15V	DC6-12V	DC6-12V
Operating Voltage Range(V DC)			
Strobe Current(A)			
Flashes/minute	65	100	80
SPL Db/1M	115±3		
Material			
Optional		Light source: tube or leds	
Color	LEN Colors: Red, Orange, Blue	Red/Blue /Amber	Blue/Red/Yellow

Bells

	FA-400	FIRE ALARM BELL	<ul style="list-style-type: none"> Ø150MM 24V, 100mA, waterproof, plastic base, could use with GST fire control panel Ø150MM 24V, 100mA, waterproof, ALUMINIUM BASE, could use with GST fire control panel Ø200MM 24V, 100mA, waterproof, plastic base, could use with GST fire control panel Ø200MM 24V, 100mA, waterproof, ALUMINIUM BASE, could use with GST fire control panel
--	--------	-----------------	--