EDIsecure® DCP350 Direct Card Printer

A HIGH-PERFORMANCE, SINGLE- AND/ OR DOUBLE-SIDED PRINTER FOR YOUR GROWING NEEDS

- Single- and/or Double-side printed cards in brilliant color with crisp, sharp graphics

- Complete modularity due to upgradable options

- Competitive printing performance with a wide ribbon selection

- Convenient, automatic front card loading and output

- User-friendly design for easy operation and maintenance

- Advanced cleaning roller system

- LCD Display with 2 LED buttons

- The perfect solutions for all kinds of applications whether a photo is printed or not

The very competitive single- and/ or double-side, edge-to-edge *EDIsecure®* DCP 350 Direct Card Printer is the perfect solution for all kinds of applications whether a photo is printed or not. With its attractive design and sturdy construction, the *EDIsecure®* DCP 350 produces high quality, professional looking ID cards and fits perfectly on any desk.

The *EDIsecure®* DCP 350 operator-friendly design has a front-facing card feeder and output hopper plus reloadable ribbon cartridges for easy handling of supplies. The *EDIsecure®* DCP 350 offers a great variety of encoding options such as contact chip, contactless chip and magnetic stripe, and is available with an Ethernet interface. With its modular assembly, the standard single-side printer can be easily upgraded to a dual-side printer at any time.

Your initial investment is well protected by its compact yet modular design and variety of available options, which eliminates the need to purchase a new system every time your printing requirements change.

THERE IS ONE FOR EVERYBODY

FEATURES

- Wide selection of ribbon types
- Front-facing, automatic card feeding and output hopper
- High capacity monochrome ribbons
- Quick ribbon change, with easy to use cartridge
- Operator replaceable printheads
- Advanced cleaning roller system to avoid scratches on cards
- Automatic ribbon detection and low ribbon warning
- Audible and visual message prompts
- LCD display with 2 LED buttons

UPGRADABLE OPTIONS

- Magnetic stripe encoding (3 Track HiCo & LoCo)
- IC (Contact) Encoding
- Contactless (Internal & External) Encoding
- Flipper Module
- Ethernet

PRO SUPPLIES

Ribbon panels	Capacity
Y M C K OP	250 cards/ ribbon (c/r)
Y M C K OP K	200 cards/ ribbon (c/r)
Y M C K OP	350 cards/ ribbon (c/r)
Y M C UV K OP	200 cards/ ribbon (c/r)

PRO MONOCHROME SUPPLIES

Ribbon	Capacity
SILVER	1200 cards/ ribbon (c/r)
GOLD	1200 cards/ ribbon (c/r)
CARBON BLACK	1200 cards/ ribbon (c/r)
CARBON BLACK OP	600 cards/ ribbon (c/r)
WHITE	1200 cards/ ribbon (c/r)
BLUE	1200 cards/ ribbon (c/r)
RED	1200 cards/ ribbon (c/r)
SCRATCH OFF	1200 cards/ ribbon (c/r)

SUPPLIES

Ribbon panels	Capacity
Y M C K OP	250 cards/ ribbon (c/r)
Y M C K OP K	200 cards/ ribbon (c/r)
Y M C UV K OP	200 cards/ ribbon (c/r)
K OP	600 cards/ ribbon (c/r)
K	1200 cards/ ribbon (c/r)

SPECIFICATIONS OF *EDIsecure® DCP 350*

Print Method	Color dye-sublimation and monochrome thermal transfer
Print Mode	Single- and/ or double-side edge-to-edge direct card printing
Print Speed	Full color: up to 144 cards per hour (single-side) Monochrome: up to 720 cards per hour (single-side)
Print Resolution	300 dpi
Printhead	Operator replaceable, 24 month warranty, no count limitation using *EDIsecure®* Cards
Card Types	All PVC and Composite PVC Cards of ISO ID-1/CR-80 size, 85.60 x 53.98mm
Card Thickness	0.3 – 1.0mm
Input Hopper Capacity	100 cards (0.76 mm)
Output Hopper Capacity	40 cards (0.76mm)
Interface	USB and optional Ethernet
Operating System Support	Windows 2000, Windows XP, Windows Vista Windows 7 (32 & 64 Bit)
Printer Dimensions (WxLxH)	Single: 170 x 420 x 195 mm (6.7" x 16.5" x 7.7"in.) Double: 170 x 510 x 195 mm (6.7" x 20" x 7.7"in.)
Weight	Approx. 5kg (11lbs.)
Power Supply	100/120 V and 220/240 V, 50/60 Hz FCC, CE, UL, GOST-R, and CCC approved, 45W

www.digital-identification.com