www.hunt.com.tw

Range Extended to Sharpen Your Vision

18X Speed Dome IP Camera

18X Zoom

2 Megapixel

Android/iOS

WINNER EXCELLENCE AWARDS 2015 secutech

2014 secutech EXCELLENCE AWARDS WINNER

Continuous Pan & Tilt

HLT-S3CDH

HUNT Hunt Electronic Co., LTD

18X Speed Dome IP Camera

HLT-S3CDH

Up to 2 Megapixel Resolution

Covering a broader view and impressively image details.

18x Optical Zoom

Greater picture quality over the smallest details.

Bank

Hotel

Airport

Lobby

Hunt Electronic Co., LTD

www.hunt.com.tw

Camera Excellence Award at Secutech

18X Speed Dome IP Camera

HLT-S3CDH

Main Features:

- 2 Megapixel 18X Speed Dome
- Support iPhone / iPad / Android

Specification

Hardware	**Image Sensor**	1/2.8" 2M Type Exmor CMOS Sensor
	Sensitivity	**Color** : 0.05 Lux (AGC ON) **B / W** : 0.005 Lux (AGC ON)
	Lens Type	18x optical zoom
	Pan / Tilt Range	Pan: 360° / Tilt: 0°~90° auto flip
	I / O	2 DI / 1 DO
	Audio	G.711(64K) and G.726(32K,24K) audio compression Input : 3.5mm phone jack Output: 3.5mm phone jack, Support 2-way.
	Power Consumption	12V DC Power consumption Max: 9.96W PoE Power consumption Max: 11.52W
	Operating Temperature	-10°C ~ 50°C
	Dimensions	149(W) x 161.3(H) x 150(Ø)
	Weight	1400 g
Network	**Network Protocol**	IPv6, IPv4, HTTP, HTTPS, SNMP, QoS/DSCP, Access list, IEEE 802.1X, RTSP, TCP/IP, UDP, SMTP, FTP, PPPoE, DHCP, DDNS, NTP, UPnP, 3GPP, SAMBA DDNS, NTP, UPnP, 3GPP, SAMBA
System	**Video Resolution**	1920x1080@30fps, 1280x720@30fps, 640x480@30fps, 320x240@30fps, 176x144@30fps
	Compression Format	H.264 / M-JPEG / MPEG4
	Security	Password protection, IP address filtering, HTTPS encrypted data transmission, 802.1X port-based authentication for network protection, QoS/DSCP

◆ SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

Hunt Electronic Co., LTD

www.hunt.com.tw

Camera Excellence Award at Secutech