Home Automation

- HSM02 Mini Door, Window Contact Detector **Z-Wave Series**



Specification Sheet

Features

- Adopt Z-Wave protocol to secure the success of wireless two-way communication
- Small in size
- With Tamperproof protection
- Easy to install
- Low battery indication
- Z-Wave V5.02
- Z-Wave Certified No. ZC08-11090007(EU)
- Auto report the open/close status and battery status
- Very low power consumption
- Certifications:

EN300220+EN301489-1/-3

EN60950-1 Part 15B+C

NCC PL0002 Based on FCC



Introduction

The Mini Door/Window contact detector consists of two parts; a Detector and a Magnet. They are designed to be fitted to doors or windows with the Magnet mounted on the opening part and the Detector mounted on the fixed frame. Opening the protected door/window will remove the magnetic field, trigger the Detector and generate an alarm condition, (if the system is armed).

The Door/Window Detector is a Z-Wave enabled device and is fully compatible with any Z-Wave enabled network.

Specification

Power	Operating Voltage Standby current Operating current Low battery voltage	3V CR2450 5 uA 30mA 2.88V
RF	Frequency Regulation Distance	868.42 MHz (EU) FCC part15.249 / EN300 220-1/ 180M open space, Minimum 30 m line of sight
Mechanical	weight Dimension (W x H x D)	23.6 g (without battery) 31x70x11.5 mm
Battery	CR2450 Battery life	620mAh 3.15 years @condition 1 0.42 year @condition 2
Environment	Operation Temperature Humidity	-10 ~ 40° C 85% RH max
Hardware	Magnetic gap(Open→Close) Magnetic gap(Close→Open)	30 mm 35 mm


Condition 1. At normal connect situation and trigger 10 times per day (every trigger means close to open or open to close)


Condition 2. At normal connect situation and trigger 260 times per day (every trigger means close to open or open to close)

^{**}Specifications are subject to change without notice

Dimension and Placement

Unit: mm





Application:

Home Automation Home Security

Local Contact:

Everspring Industry Co., Ltd.

3F., No. 50, Sec 1, Zhonghua Rd., Tucheng Dist.,

New Taipei City 23666, Taiwan

TEL: +886-2-2260-6868 FAX: +886-2-2260-1313

Website: www.everspringindustry.com

Service Support: sales@everspring.com