

室外紅外線攝影機

特性：

- * 24-hour operational camera with perfect picture performance.
- * IR camera built-in 31 IR LEDs for 20-25m range in dark view.
- * Unique looks for outdoor / indoor application.
- * Packing camera, lens, bracket as a set.
- * Water resistant of aluminum die-cast pass IP 66 test.
- * Easy to install.



Model	GC-R336
Image device	1/3" color CCD sensor interline
Effective picture elements	NTSC 510(H) x 492(V) PAL 500(H) x 582(V)
Scanning system	2:1 interlace
Synchronizing system	Internal
Horizontal resolution	More than 380 TV lines
Electronic shutter control	Auto-Electronic Shutter (1/60~1/100000 sec)NTSC; (1/50~1/100000 sec)PAL
Gamma	0.45
Minimum illumination	1.0 Lux/F1.8 IR on: 0 Lux
Video output level	1Vp-p / 75Ω
Video S/N ratio	48 dB (AGC off)
White balance	Auto (2500°K~9500°K)
Backlight compensation	Yes
Storage temperature	-30°C~80°C
Operating temperature	-10°C~50°C
Power requirements	DC 12V±10%
Power consumption	200mA
AGC function	AUTO
Number of IR LED	31 PCS
Illumination distance	20-25m
Dimensions	117 (L) X 83 (W) X 83 (H) mm
Weight	500g
Lens standard	4.6mm Option:6.0mm/8.0mm/12.0mm/F1.8