

High Speed Dome Camera (Indoor Type)

Features

- * Artistic & durable aluminum alloy shell
- * Integrated design for rotation part, precision structure and reliable running
- * Fast-mount connection for convenient installation and maintenance outdoor
- * Within integration high resolution camera, multi-protocol coding board, high compatibility with control systems



Technical Data

Model No.	APG-KD6/216N	APG-KD6/230N	APG-KD6/300N	APG-KD6/370N
Dome Address	0~255			
Pan Rotation	360° continued rotation			
Tilt Rotation	0°~90°, 180°(auto rotation)			
Manual Pan Speed	0.1~300°/S			
Manual Tilt Speed	0.1~120°/S			
Preset Position Speed	400°/S			
Preset Position Accuracy	±0.10°			
Preset Position	128pcs			
Zoom Camera	SONY 480CP	Samsung SDM-231	Samsung SDM-330	Samsung SDM-375
	18X Optical Zoom	23X Optical Zoom	30X Optical Zoom	37X Optical Zoom
	480TVLINE	540TVLINE	540TVLINE	550TVLINE
Menu	Multilingual (English,Chinese,German,French,Russian,Italian,Spanish)			
Function Display	Yes			
Account Management	Password locked setting			
User Permission Management	Available			
Date & Time setting and display	Date, Time setting and display			
Mission Setting	8pcs, like: operation mode, function setting etc.			
Scheduled Mode	Scheduled Setting			
Alarm Input	8 groups			
Alarm Output	2 groups			
Temperature Setting & Display	Temperature Alarm, Temperature Shutdown Setting, Alarm Warning, Temperature Display			
Aiming Function	Available			
Real-time Position Display	Real-time Position Display			
Programmable Mask Section	8pcs			
Programmable Section Display	8 Groups Programmable Real Time			
Memory Function	Available			
PTZ Tours	3pcs (Pan/Tilt/Zoom, record up to 120sec. each)			

Return Function	Last Operation Back
Programmable Vector Tour	6pcs (including scanning speed, dwell time, preset points embedded, vector scanning and PTZ tour)
Protocol	PELCO D/P, Actiontop, Alec
Auto Pan Scanning	Intelligent Speed Unlimited Scanning
Three-dimensional Tour	Intelligent Speed Unlimited Scanning
Tele lens Speed	Intelligent Speed Adjustment
Memory at Power Off	Save at power off, auto-awake by patrol
Image Freezing Function	Available
Manual Continuing Auto Scanning	unlimited
IP66 Protection	NON
Operation Temperature	0°C~50°C
Operation Humidity	0%~90% (non-condensing)
Heater	NON
Power Requirements	24VAC 2A 60Hz/50Hz
Power Consumption	20W
Interface	RS485 (+/-)
Wiring	Coaxial Cable

High Speed Dome Camera (Outdoor Type)

Features

- * Artistic & durable aluminum alloy shell
- * Integrated design for rotation part, precision structure and reliable running
- * Fast-mount connection for convenient installation and maintenance outdoor
- * Within integration high resolution camera, multi-protocol coding board, high compatibility with control systems



Technical Data

Model No.	APG-KD6/216NW	APG-KD6/230NW	APG-KD6/300NW	APG-KD6/370NW
Dome Address	0~255			
Pan Rotation	360° continued rotation			
Tilt Rotation	0°~90°, 180°(auto rotation)			
Manual Pan Speed	0.1~300°/S			
Manual Tilt Speed	0.1~120°/S			
Preset Position Speed	400°/S			
Preset Position Accuracy	±0.10°			
Preset Position	128pcs			
Zoom Camera	SONY 480CP	Samsung SDM-231	Samsung SDM-330	Samsung SDM-375
	18X Optical Zoom	23X Optical Zoom	30X Optical Zoom	37X Optical Zoom
	480TVLINE	540TVLINE	540TVLINE	550TVLINE
Menu	Multilingual (English,Chinese,German,French,Russian,Italian,Spanish)			
Function Display	Yes			
Account Management	Password locked setting			
User Permission Management	Available			
Date & Time setting and display	Date, Time setting and display			
Mission Setting	8pcs, like: operation mode, function setting etc.			
Scheduled Mode	Scheduled Setting			
Alarm Input	8 groups			
Alarm Output	2 groups			
Temperature Setting & Display	Temperature Alarm, Temperature Shutdown Setting, Alarm Warning, Temperature Display			
Aiming Function	Available			
Real-time Position Display	Real-time Position Display			
Programmable Mask Section	8pcs			
Programmable Section Display	8 Groups Programmable Real Time			
Memory Function	Available			
PTZ Tours	3pcs (Pan/Tilt/Zoom, record up to 120sec. each)			
Return Function	Last Operation Back			

Programmable Vector Tour	6pcs (including scanning speed, dwell time, preset points embedded, vector scanning and PTZ tour)
Protocol	PELCO D/P, Actiontop, Alec
Auto Pan Scanning	Intelligent Speed Unlimited Scanning
Three-dimensional Tour	Intelligent Speed Unlimited Scanning
Tele lens Speed	Intelligent Speed Adjustment
Memory at Power Off	Save at power off, auto-awake by patrol
Image Freezing Function	Available
Manual Continuing Auto Scanning	unlimited
IP66 Protection	YES
Operation Temperature	-30°C~+60°C
Operation Humidity	0%~90% (non-condensing)
Heater	6°C (ON) 14°C (OFF)
Power Requirements	24VAC 2A 60Hz/50Hz
Power Consumption	35W
Interface	RS485 (+/-)
Wiring	Coaxial Cable

100M IR High Speed Dome Camera (Outdoor Type)

Features

- * Artistic & durable aluminum alloy shell
- * Integrated design for rotation part, precision structure and reliable running
- * Fast-mount connection for convenient installation and maintenance outdoor
- * Within integration high resolution camera, multi-protocol coding board, high compatibility with control systems



Technical Data

Model No.	APG-IRKD7/216NW
Dome Address	0~255
Pan Rotation	360° continued rotation
Tilt Rotation	0°~90°, 180°(auto rotation)
Manual Pan Speed	0.1~220°/S
Manual Tilt Speed	0.1~120°/S
Preset Position Speed	400°/S
Preset Position Accuracy	±0.10°
Preset Position	128pcs
Zoom Camera	SONY 480CP
	18X Optical Zoom
	480TVLINE
IR Distance	100M
Menu	Multilingual (English,Chinese,German,French,Russian,Italian,Spanish)
Function Display	Yes
Account Management	Password locked setting
User Permission Management	Available
Date & Time setting and display	Date, Time setting and display
Mission Setting	8pcs, like: operation mode, function setting etc.
Scheduled Mode	Scheduled Setting
Alarm Input	8 groups
Alarm Output	2 groups
Temperature Setting & Display	Temperature Alarm, Temperature Shutdown Setting, Alarm Warning, Temperature Display
Aiming Function	Available
Real-time Position Display	Real-time Position Display
Programmable Mask Section	8pcs
Programmable Section Display	8 Groups Programmable Real Time
Memory Function	Available
PTZ Tours	3pcs (Pan/Tilt/Zoom, record up to 120sec. each)
Return Function	Last Operation Back

Programmable Vector Tour	6pcs (including scanning speed, dwell time, preset points embedded, vector scanning and PTZ tour)
Protocol	PELCO D/P, Actiontop, Alec
Auto Pan Scanning	Intelligent Speed Unlimited Scanning
Three-dimensional Tour	Intelligent Speed Unlimited Scanning
Tele lens Speed	Intelligent Speed Adjustment
Memory at Power Off	Save at power off, auto-awake by patrol
Image Freezing Function	Available
Manual Continuing Auto Scanning	unlimited
IP66 Protection	YES
Operation Temperature	-30°C~+60°C
Operation Humidity	0%~90% (non-condensing)
Heater	6°C (ON) 14°C (OFF)
Power Requirements	12VDC 5A 60Hz/50Hz
Power Consumption	35W
Interface	RS485 (+/-)
Wiring	Coaxial Cable

High Speed Mini-dome Camera

Features

- *3.8" complete metal shell
- *Motor-driver
- *Including 10X zoom integrated camera
- *Wall bracket (standard), embedded mount (optional)



Technical Data

Model No.	APG-KM/100N (Indoor)	APG-KM/100NW (Outdoor)
Dome Address	0~255	
Pan Rotation	360° continued rotation	
Tilt Rotation	0°~90°, 180°(auto rotation)	
Manual Pan Speed	0.1~240°/S	
Manual Tilt Speed	0.1~120°/S	
Preset Position Speed	300°/S	
Preset Position Accuracy	±0.10°	
Preset Position	128pcs	
Zoom Camera	SAMSUNG SDM-100	
	10X Optical Zoom	
	540TVLINE	
Programmable Vector Tour	6pcs (including scanning speed, dwell time, preset points embedded, vector scanning and PTZ tour)	
Protocol	PELCO D/P	
Auto Pan Scanning	Intelligent Speed Unlimited Scanning	
Memory at Power Off	Save at power off, auto-awake by patrol	
Preset Position Return	Static Preset Position Return	
Image Freezing Function	Available	
Manual Continuing Auto Scanning	unlimited	
IP66 Protection	NON	YES
Operation Temperature	0°C~+50°C	-30°C~+60°C
Operation Humidity	0%~90% (non-condensing)	
Power Requirements	24VAC 1000mA	
Power Consumption	6W	
Interface	RS485 (+/-)	