

Unique Economical Weather-proof IR Camera



Unique Design
520TVL
DSP D/N
36Pcs IR LED



Features:

- 1/3" Sony Ex-view CCD
- 3 Crystal Layer Filter
- Built-in 6mm Lens
- 520TV Line
- 0.01 Lux(B/W)
- 36 Pcs High Intensity LED's
- Unique aluminium housing
- Visible range up to 30m in total darkness
- Color Kill(When IR LEDS are on, the image is forced to pure B/W)
- NTSC/PAL System



Specification

Model Number	HD-IR326LA-DAPN	HD-IR326AA-DAPN	HD-IR326UA-DAPN
Type	Color / Monochrome (D/N)		
Signal System	NTSC/PAL		
Filter (Crystal)	3 LPF layer	2 LPF layer	
Image sensor	1/3" SONY Ex-view CCD	1/3" SONY Color CCD	1/3" SHARP Color CCD
Pixel	N:811H × 508V P:795H × 596V	N: 500H × 582V P: 537H × 597V	
Resolution	520TVL	420TVL	
Mini Illumination	0.01Lux	0.1Lux	
Vertical Frequency	NTSC: 59.94Hz PAL: 50.00Hz		
Horizontal Frequency	NTSC: 15.734KHz PAL: 15.625KHz		
Clock Frequency	NTSC: 28.636MHz PAL: 28.375MHz		
Scanning System	2:1 Interface		
Sync System	Internal		
S/N Ratio(AGC OFF)	58db	48db	42db
Electronic Shutter	N: 1/60-1/120,000S P: 1/50-1/120,000S		
Lens	6mm IR Lens		
IR LED	36Pcs High Intensity		
IR Effect Distance	30M		25M
White Balance	ATW		
BLC	ON		
Mirror	OFF		NC
Gain Control	Max Gain 18db / Super Gain 30db		
Gamma	0.45		
Video Output	1V p-p,75 Ω		
Audio Output	2V p-p,75 Ω		
Power Supply	DC10-14V		
Current Consumption(Max)	350mA		
Dimension	140x70x70mm		
Weight	630g		
Storage Temperature	-30 ~ +60℃		
Operating Temperature	-10 ~ +45℃		

