

5.0MP IP Network plastic IR dome camera

Features:

- * H.265+ MainProfile, JPEG Capture
- * Onvif 2.0 Supported
- * Connect with Hybrid DVR, NVR
- * Support mobile Surveillance such as (iPhone, Android).
- * Support cloud service, P2P IP camera

≥1
\$0.00

em No.IPC-DIR1C13-2

IOQ1 /

Description

Specification:

Model No.	IPC-DIR1C13-2
Pixel:	5.0/4.0MP
Image Sensor	1/2.8" CMOS (550AI+SONY IMX 335)
Frame Rate	50Hz: 25fps (2560 X1920) / 60Hz: 30fps (2560 X 1920)
Lens:	2.8mm
IR Leds:	3 ϕ 14 IR Array Leds
Audio	Optional
IR Distance:	10-15 Meters
The Output Of Compression Rate	32 Kbps~2Mbps
Image Setting	Saturation, Brightness, Contrast Could Be Ajustable Through The IE Browser Or CMS
Intelligent Alarm	Motion Detection, Video Lost, Network Cut Down, IP Address Conflict, Memory Is Full, The Memory.with Wrong
Network Protocol	TCP/IP,HTTP,DHCP,DNS,DDNS, PPPoE,SMTP,NTP (HTTPS, SIP , 802.1x,Ipv6 Optional)
General Function	Flicker, Dual Stream, Heartbeat, Password Protection
Communication	1 Pc RJ45 10M/100M Adaptive Ethernet Port
Port Cable:	DC12V + RJ45 10M/100M Ethernet
Power Supply	DC12V \pm 10%
POE	No
Housing Color	Plastic, White
WorkingTemperature And Humidity	-10°C~60°C, Humidity Is Less Than 90% (No Condensation)
Dimension(Mm)	ϕ 94 X 69(H) Mm
G.W	0.25KG

Have more questions about this product?



Scan the QR code with your phone, or visit the URL

<https://www.surwaytech.com/>

Have more questions about this product?

6/F, Minde Building, No.2 Minde Road, Minzhi Street, Long Hua District, Shenzhen, Guangdong Province, China

+86-755-28446822

Sales@surwaytech.com