



Shenzhen Lingbao Electronics Co., Ltd

Add: 5F, 9th Building, Sunshine industrial estate, Xi-li town, Nanshan District, Shenzhen, China

<http://www.made-in-china.com/showroom/china-alarm>

<http://www.lb-ak.com>

Tel: 86-0755-29810559-811

Fax: 86-0755-26518828-808

Mobile: 86-15899879182

Contact: Lily

Email/MSN: lbak-117@hotmail.com

Skype: lilylbak

Wireless burglar alarm system



Technical specifications:

Alarm control panel:

- (a) operating voltage: DC9V
- (b) Average power: AC/DC exchanger 300mA
- (c) operating Frequency: 433.92 MHZ \pm 2KHZ/315 MHZ

Remote controller

- (a) operating voltage: DC12V
- (b) Emission Distance: \geq 30m
- (c) operating Frequency: 433.92 MHZ \pm 2KHZ/315 MHZ

Wireless Magnetic Door detector

- (a) operating voltage: DC12V
- (b) Emission Distance: \geq 30m
- (c) operating Frequency: 433.92 MHZ \pm 2KHZ/315 MHZ

Wireless panic button

- (a) operating voltage: DC12V
- (b) Emission Distance: \geq 30m
- (c) operating Frequency: 433.92 MHZ \pm 2KHZ/315 MHZ

Wireless vibration sensor

- (a) operating voltage: DC12V
- (b) Emission Distance: \geq 30m
- (c) operating Frequency: 433.92 MHZ \pm 2KHZ/315 MHZ

Wireless external siren

- (a) operating voltage: DC6~12V, 300mA
- (b) Emission Distance: \geq 30m
- (c) Operating Frequency: 433.92 MHZ \pm 2KHZ/315 MHZ