

KARASSN SECURITY PROTECTION ELECTRONICS CO., LTD.

Karassn Co., Road 1, Economic & Technologic Zone, Quanzhou, Fujian, China www.karassn.com

Model No.	Products Photo	Package Photo
KB-A1188(433SF/GSM-1) Network Alarm System		A contract of the contract of
Panel size:L*W*H(mm)	258 * 260 * 77	

Brief Instruction

A Network Industrial Alarm System is the dual-network burglar alarm system with design of a detachable keypad. It is adopts with wired telphone network and GSM wireless network to transmit the alarm signal. There are 6 wireless and 6 wired zones. It can be collocated with various type of wire/ wireless sensors, and consist of security protection system of Burglar, Fire, Gas and Emergency status. 8 groups of telephone number can be set, Once there is alarm occurring, the alarm panel will activate the siren on-site to make sound and the pre-set number will be dialed.

It is suitable for security service, business places, financial constitutions and enterprises

Main Function

- 1). Detachable keypad with alarm panel
- 2). 6 wireless + 6 wired zones
- 3). 3 level of codes access
- 4). Support CID
- 5). Support close arm type
- 6). Support report of patrolling
- 7). Remote operation via control center
- 8). Re-dialing function ensure reliability
- 9). Home Arm and Overall Arm, the zones list of Home Arm can be defined at will
- 10). Anti-false intelligent alarm function
- 11). 8 pre-set numbers can be set
- 12). Remote operation via mobile phone
- 13). Wired zone respond speed (100ms-900ms)
- 14). Trouble of telephone line and GSM module will send alert
- 15). Two timers can be set to Arm/ Disarm corresponding zones independently
- 16). Back up rechargeablt battery ensure stability
- 17). GSM + PSTN
- 18). SD module and wired board is for option

GSM Module

The GSM alarm module is a network intelligent alarm terminal device, which is composed of mainstay industry GSM module and the communication carrier by GSM network. It has different ways of combination for alarm, such as make alarm to ADEMCO Contact ID alarm center, Dialing voice, English SMS, Timer communication, etc. It is endued with precise and timely transmission in alarm information. Moreover, it has the advantages of little-influence by environment, low rate of false alarm, safety, convenient installation and environmental protection. Therefore, it can be the strong shield for your home.

Main Function

- 1). Support ADEMCO CID alarm center, Dialing voice, English SMS, Timer communication
- Modular cordwood design
- 3). English message hint for operation and alarm.
- 4). Different alarm ways to combine: center, SMS, dialing, Timer, etc
- 5). Various ways of Arm/ Disarm, which including SMS, Dialing or Ringing
- 6). Multi-level of protection, such as code protection, classification operation, and phone firewall, etc
- 7). Assign an English name to every zone. It is convenient for user to indentify the position
- 8). 3 groups of program phones and 8 groups of alarm phones.
- 9). Sending start-up SMS, sending information and sending report ON/ OFF are for option.
- 10). The dialing/ringing time can be set
- 11). 20s voice can be recorded
- 12). All the settings are conserved in the memory card of GSM module to avoid losing when power off
- 13). SMS can query the setting at all times
- 14). It can conserve and SMS query with 100 pieces of alarm event log with the function of 'Black Box'

,		
Standard Kit	1 Panel 1PC 433MHz Transceiver Modules 2PCS KS-12B Controller 1PC GSM Module	
Package weight	3. 1KGS	
Carton	10PCS	
MOQ	50PCS	
Price	USD92. 06	