



Mouse





GUI






Main Features

- H.264 video compression
- 240 CIF fps recording frame rate
- Video files sent along with email alert and notification by MSN
- SATA II compatible HDD & E-SATA for external HDD
- Intelligent 3G/GPRS mobile surveillance
- Support smart search function for faster and easier playback retrieval
- Picture-in-picture display & channel screen popup on motion/sensor
- Optional 1-to-8 remote controller for access up to 8 DVRs with one single remote controller
- Role-based multiple network users access to exclusive channel view & operation
- Provide optional touch screen display integrated with LCD
- Provide disk array option with mirror functionality to provide additional storage archival without missing any display images
- Provide Graphical User Interface (GUI) and mouse access for easier and user friendly configuration and operation
- Remote independent operation

Interface



1-9 Function Keys	10-13 Direction Keys	14 LED Display	15 IR Sensor
16 USB 2.0 Port	17 CD/DVD-RW		

Back Panel Layout (5) 0 0

1 MAIN Monitor	2 SPOT Monitor	3 VIDEO IN	4 AUDIO IN
5 AUDIO OUT	6 VGA	7 E-SATA	8 Fan
9 EXTERNAL I/O	10 LAN	11 NTSC / PAL Switch	12 DC 12V

Specifications

Model No.		SDVR-810				
			Video			
Mode			Pentaplex (Live, Record, Playback, Backup, and			
	Mode		Network)			
Video Input			BNCx8 1.0 Vp-p±10% Composite, 75 Balanced			
Video Loop Out			N/A			
	Main Monitor		BNCx1 2Vp-p Composite, 75 Balanced			
Video Output	Spot Monitor		BNCx1			
	S-Video		N/A			
	VGA (Optional)		VGAx1, 1024x768 pixels			
Acadia Innest			Audio			
Audio Input Audio Output			RCAx4 RCAx1			
Audio Output Audio Backup			YES			
Audio Compressi	on		G.711			
Addio Compressi	011		Display			
Image System			NTSC	PAL		
	n 9		NIGO	FAL		
Rate	Display Resolution & Rate		240fps (720x480)	200fps (720x576)		
Split Screen			1/4/8/SEQ			
Mode			Digital Zoomx2, PIP, Auto	SEQ		
			Recording			
Compression Typ	ре		H.264 (Internet Transmission: H.264)			
Recording Resol	ution &	D1	up to 60fps (720x480)	up to 50fps (720x576)		
Rate	ation &	Half D1	up to 120fps (720x240)	up to 100fps (720x288)		
		CIF	up to 240fps (352x240)	up to 200fps (352x288)		
Image Quality		5 Levels (Highest, High, Normal, Low, Lowest)				
Recording Mode			Normal, Event (Motion, Alarm), Schedule, Holiday			
Playback						
Screen Display			1, 4, 8			
Playback Resolu	tion 0	D1	up to 30fps (720x480)	up to 25fps (720x576)		
Rate	uon &	Half D1	up to 60fps (720x240)	up to 50fps (720x288)		
- tato		CIF	up to 120fps (352x240)	up to 100fps (352x288)		
Playback Speed	Playback Speed		Normal, REW, FF (2x, 8x, 32x, 64x), Pause			
Search Method Time, Event						
	Storage & Backup Device					
Internal HDD Support (SATA/SATA II)			Support up to 2 HDDs or 1 HDD &1 internal DVD-RW			
External SATA		YES for RAID				
Network		Remote Backup				
USB Backup	USB Backup		1 at Front Panel			
CD/DVD-RW Backup		SATA Interface				

OSD & DVR Control					
GUI	YES				
Multi Language	12 (English, French, German, Greek, Japanese, Italian, Polish, Portuguese, Russian, Spanish, Simplified Chinese, Traditional Chinese)				
USB Mouse	YES				
IR Remote Control	YES & 1-to-8 Remote Control (Optional)				
DVR Control Panel	YES				
Remote Software	Licensed Software Application, IE Browser & CMS				
Touch Panel	Supports USB Touch Panel				
	Communication				
Ethernet	1 RJ45, 10/100 Mbps				
Network Service	TCP/IP, SMTP, HTTP, DHCP, ADSL, LAN, DDNS				
Multi-Remote Client	YES (5 Clients Accessible)				
3G/GPRS	Supports Windows Mobile 5.0/6.0, Symbian & iPhone				
	Alarm				
Sensor Input	8 In (NO/NC)				
Alarm Output	1 Relay Out (NO/NC)				
Motion Detection	YES (16x12 Grids per Camera for All Channels)				
Motion Detection Sensitivity	1~15				
Video Loss Detection	YES				
Pre-alarm Recording	16MB (10 sec)				
Post-alarm Recording	1-999 sec				
Buzzer	YES				
Remote Alarm Notification	J-PEG File sent by e-mail; Message Notified by MSN & 3G Mobile Phone				
Setu	up & Other Functions				
PTZ Control	Supports PELCO-D, PELCO-P, KND, Li-Lin, LG, Samsung, AV Tech				
RS-485	YES				
Password Control	YES				
Key-lock	YES				
Firmware Upgrade	via USB				
Others					
OS	Embedded Linux				
Power Input	External Adaptor, AC100-240V/in, DC 12V(5A/60W)				
Dimension	430x293x55(mm)				
Weight	3kg (Including 1 HDD or CD/DVD-RW)				
Operation Temperature	5°C~ + 40°C				
Humidity	Less than 90%				
Watermark	N/A				
Recovery	Watchdog				
Certificates	CE, FCC, RoHS				
SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE					

