

# Premium Real-Time Recording Standard H.264 Stand-Alone! EOS Series



## Main Features

- Full Graphic User Interface (Multiple language support)
- Individual Channel Recording (Resolution, Frame rates and Quality)
- Easy Operation by USB mouse / Front Keys / Remote Control
- De-Interlacing feature in DVR Itself
- System Automatic-Rebooting by Itself for Watch-Dog

- 2 x SATA HDD Internal Bay (2xHDD+1ODD)
- Multiple VGA Resolution: 800x600, 1024x768, 1280x1024
- 2 Video Out (Composite, VGA)
- Backup via DVD-RW, USB Memory Stick & USB HDD


- Real Pentaplex Operation
- Recording & Alarm-Out Scheduling
- Pre / Post / Extra-Alarm Recording
- Dual-Stream (Local Recording & Network Transmission)
- I.E Web-Browsing, CMS (DDNS and Multi Port support)
- 3G Mobile Phone Viewer

## Specification


MODEL		EOS-0412	EOC-0824	EOS-1648
Compression Algorithm		Video : H.264, Audio : G723		
HDD Bay		2 x SATA HDD or 2 x SATA HDD & 1 x ODD, Max:2TB/HDD		
Operating System		Embedded Linux		
Video	Input	4 CH	8 CH	16 CH
	Loop-Out	X	X	X
Video Out	Monitor	1 x Composite & 1 x VGA		
	VGA Resolution	VGA Resolution : 800x600, 1024x768 & 1280x1024 (Selectable)		
Live Display Modes		1, 4 & PIP	1, 4, 9 & PIP, POP	1, 4, 9, 16 & PIP, POP
Recording Speed (NTSC/PAL)	352x240/288(CIF)	120/100 fps	240/200 fps	480/400 fps
	720x240/288(2CIF)	120/100 fps	240/200 fps	240/200 fps
	720x480/576(D1)	120/100 fps	120/100 fps	120/100 fps
Recording Modes		Continuous, Scheduled, Sensor-Activated & Motion Detection Recording Pre & Post Alarm Recording, Emergency Recording		
Playback & Backup	Speed	x1, x8, x32, x64, x128		
	Search	Intelli-Search by Time Bar, Calendar, Event and First/Last Search		
	Backup Device	USB Memory Stick/HDD, DVD-RW & Network by CMS		
Audio Input / Output		4 In / 1 Out	8 In / 1 Out	8 In / 1 Out
Sensor Input / Alarm Output		4 In / 4 Out	8 In / 4 Out	16 In / 4 Out
Port		4 x USB, 2 x RS-485(P/TZ), 1 x RS-232		
LAN		10/100 Base-Tx Ethernet (RJ45) – Static / DHCP / DDNS		
Network	Transmission	Video Dual-Stream (Local recording & Network Transmission)		
	C.M.S	Live Monitoring, Playback and Backup, PTZ Control, Local DVR Reboot		
	Web (IE)	Live Monitoring, Playback, Snapshot and PTZ Control		
Other Functions		Multi-Language, Firmware Upgrade by USB & Network Configuration Import & Export, Water-Mark, Alarm out for Video Loss & Events Email-Notification/Alarm-out/Buzzer for Events, Warning for System Over-Temp		
Power		DC12V, 5A		
Storage Temperature and Humidity		-20~60°C / 20~95% RH		
Operating Temperature and Humidity		5~40°C / 20~80% RH		
Dimension (WxDxH)				
Certification		CE, FCC, MIC & RoHS		

## Rear Design


MODEL:EOS-0412



MODEL:EOS-0824



MODEL:EOS-1648



## Configuration

