

# SDI

www.hsintek.com.tw

**Solution Provider**

## »» 3G-SDI Monitor

## »» SDI-PVM Monitor

- [3G] 1080P50/60(4:2:2);  
[HD] 720P@50/60Hz, 1080i@50/60Hz;1080P@25/30Hz  
[SD] NTSC / 60 Hz, PAL / 50Hz
- LED Backlight.
- Support Digital/Video Signal.
- Support 1920 x 1080 Full HD High Quality.
- VESA Standard Bracket.
- Aluminum Panel Frame, Metal Case.
- Screen Protector(Anti-Blur/Image Auto Move).
- Including 1 CH SDI IN & OUT / 2 CH Composite Video IN & Out  
Full HD Input /S-Video IN/ D-Sub IN and 2 CH Audio IN&OUT.  
SDI Video Support:



## »» HD-SDI Camera

- Waterproof IR Camera/Vandal IR Dome Camera
- Full HD Mega Pixel ( 1080P).
- 2D/3D Digital Noise Reduction.
- D-WDR(Digital Wide Dynamic Range).
- Motion Object Detection.
- Lens Shading Compensation.
- D-Zoom.
- NTSC/PAL Mode Switchable.
- CVBS & SDI 2-Way Output.  
Building IR-Cut Filter.

## »» CVBS<->SDI Tester

- Supported:  
1080p/60,1080p/50,1080p/30,1080p/25,  
1080i/60,1080i/50,  
720p/60,720p/50.



HSINTEK ELECTRONICS CO.,LTD

Tel: 886-3-3239123 Http://www.hsintek.com.tw

Fax:886-3-3239105 E-mail: Marketing@msa.hsintek.com.tw



ISO 9001:2008  
CNS 12681



 Hsintek 