

Digital Intelligent Heavy-load Pan Tilt J-IP-7240-DL



Features

- High intensity aluminum alloy casing, waterproof, heat resistant, ageing resistance, anti-corrosion. Designed for all-weather environment.
- Adopts DC brushless machine and the drive mode of gear reducer, insure stability, promote response, flexible operation, energy saving and RoHS, can use solar power for electricity.
- IP PTZ with RJ45 port
- Built-in intelligent decoder, high precision orientation, tour through presets in groups, realize the closed loop control of position velocity, no self-checking after power-on.
- Auto routing inspection function
- Auto scan function/Three-dimensional scan between two presets
- With the data returning function, can be linked with other boot device
- Multi-mast the PTZ, flexible, convenient. Prompt response without lag.
- Protection grade IP66, special surface treatment can meet three proofing requirements

Technical Data

Input voltage	AC24(±15%) 50/60Hz
Consumed power	≤200W
Turn Angle	
Pan	0 to 360 degrees
Tilt	-60 to+ 60 degrees
Turn Speed	
Pan	1-12 degrees/s
Tilt	0.5-6 degrees/s
Presets	Max 220
Presets Precision	± 0.1 degree
Communicate Format	RS-485
Communicate Protocol	Pelco P,D

Baud Rate	1200/2400/4800/9600BPS
Address	1-255
Work Temperature	-30 - +55°C
Maximum Loading	40kg
Weight	14.5kg

Dimension

