

## 25-inch CCTV camera housing J-CH-4525-SFH



### Features:

- optional visible light cameras, thermography, infrared lights, laser device
- Built-in adjustable mounting slide plate
- Built-in heater&fan auto temperature control circuit
- Provides protection from dust and water, anti-corrosion, heat-resistant,suitable for all-weather outdoor environment

### Technical data:

Input voltage	AC24V( $\pm 10\%$ ) 50/60Hz
Power consumption	Heater $\leq 60W$ Fan $\leq 2W$
Automatic temperature control	Heater Open: $5^{\circ}C \pm 5^{\circ}C$ Close: $15^{\circ}C \pm 5^{\circ}C$ Fan Open: $40^{\circ}C \pm 5^{\circ}C$ Close: $25^{\circ}C \pm 5^{\circ}C$
Open mode	Back-opened
Material	Body: aluminum alloy/Viewing window: optical glass
Operating ambient temperature	$-35^{\circ}C \sim +65^{\circ}C$ (with Heating elements)
Operating ambient humidity	$< 90\%$ (without condensing agent, under heating conditions)
Maximum size of camera installation	550mmX188mmX140mm
Both sides of the space	720mmX280mmX207mm
Recommend pan tilt	J-IP-7240-DL; J-IP-4250-DL
Installation environment	Indoor and outdoor
IP standard	IP66