

Premium Real-Time Recording High-End H.264 Stand-Alone!

NTS Series



Main Features

- Full Graphic User Interface (Multiple language support)
- Individual Channel Recording (Resolution, Frame rates and Quality)
- Easy Operation by USB mouse / Front Keys / Remote Control
- De-Interlacing feature in DVR Itself
- System Automatic-Rebooting by Itself for Watch-Dog

- 4 x SATA HDD Internal Bay (3 x HDD & 1 x ODD)
- Multiple VGA Resolution: 800x600, 1024x768, 1280x1024
- Backup via DVD-RW, USB Memory Stick & USB HDD
- Recording & Alarm-Out Scheduling
- Pre / Post / Extra-Alarm Recording


- Real Pentaplex Operation
- Dual-Stream (Local Recording & Network Transmission)
- I.E Web-Browsing, CMS (DDNS and Multi Port support)
- Alert for System Over-Temperature
- 3G Mobile Phone Viewer

Specification


MODEL		NTS-0824	NTS-1648
Compression Algorithm		Video : H.264, Audio : G723	
HDD Bay		4 x SATA HDD or 3 x SATA HDD & 1 x ODD	
Operating System		Embedded Linux	
Video	Input	8 Ch	16 Ch
	Loop-Out	8 Ch	16 Ch
Video Out	Monitor	1 x Composite, 1 x VGA & 1 x Spot Monitor	
	VGA Resolution	VGA Resolution : 800x600, 1024x768 & 1280x1024 (Selectable)	
Live Display Modes		1, 4, 9 & PIP, POP	1, 4, 9, 16 & PIP, POP
Recording Speed (NTSC/PAL)	352x240/288(CIF)	240/200 fps	480/400 fps
	720x240/288(2CIF)	240/200 fps	480/400 fps
	720x480/576(D1)	240/200 fps	240/200 fps
Recording Modes		Continuous, Scheduled, Sensor-Activated & Motion Detection Recording Pre & Post Alarm Recording, Emergency Recording	
Playback & Backup	Speed	x1, x8, x32, x64, x128	
	Search	Intelli-Search by Time Bar, Calendar, Event and First/Last Search	
	Backup Device	USB Memory Stick/HDD, DVD-RW & Network by CMS	
Audio Input / Output		8 In / 1 Out	16 In / 1 Out
Sensor Input / Alarm Output		8 In / 4 Out	16 In / 4 Out
Port		4 x USB, 2 x RS-485(P/TZ), 1 x RS-232	
LAN		10/100 Base-Tx Ethernet (RJ45) – Static / DHCP / DDNS	
Network	Transmission	Video Dual-Stream (Local recording & Network Transmission)	
	C.M.S	Live Monitoring, Playback and Backup, PTZ Control, Local DVR Reboot	
	Web (IE)	Live Monitoring, Playback, Snapshot and PTZ Control	
Other Functions		Multi-Language, Firmware Upgrade by USB & Network Configuration Import & Export, Water-Mark, Alarm out for Video Loss & Events Email-Notification/Alarm-out/Buzzer for Events, Warning for System Over-Temp	
Power		DC12V, 6.67A	
Storage Temperature and Humidity		-20~60°C / 20~95% RH	
Operating Temperature and Humidity		5~40°C / 20~80% RH	
Packing Dimension (WxDxH)		430 x 90 x 428, Packing: 520 x 215 x 520 (mm)	
Certification		CE, FCC, MIC & RoHS	

Rear Design

MODEL:NTS-0824



MODEL:NTS-1648



Configuration

