





# Feptel Enterprise


MSN: feptle@hotmail.com      Email: telan@feptel.com


Company website: www.feptel.com Tel:86-755-28876034


## Access controller

Model No.:	MOQ	USD	FEATURE	Picture
<b>F2</b>			1 Waterproof metal access fingerprint recognition ;	 95mm*56mm*35mm
			By TM cards to manage users	
			3 Local capacity: 200 fingerprint templates;	
			4 Standalone fingerprint access controls and fingerprint reader;	
			5 Attractive outlook and compact module design	


Model No.:	MOQ	USD	FEATURE	Picture
<b>A2</b>			EM Access control Support 1000 users Add or delete card by master cards	
<b>A5</b>			Memory, and can keep 500 cards and 510 the user's password Has three ways to open the door. Cards, passwords, card add No card, you can set a password to open the door With a doorbell button, and Button to open contact	
<b>A6</b>			A square shell, elegant designs Memory, and can keep 2000 cards and 2010 the user's password Has three ways to open the door. Cards, passwords, card & password No card, you can set a password to open the door With a doorbell button, and Button to open contact Outside Can be connected to 1 reader	

<b>A8</b>			Waterproof designs Support 1000 users 2 relays for access control and alarm Door open detection Support door bell Support only keypad	
-----------	--	--	--	---

Model No.:	MOQ	USD	FEATURE	Picture
<b>FC-2011</b>			Door control 1 door	 160mm *106mm 273mm*228mm*65mm
			2 reader can be connected	
			Control of Memory up to 20,000 Users	
			up to 100,000 Event Buffers	
			Network Communication via RS232 / RS485	
			TCP/IP optional	

Model No.:	MOQ	USD	FEATURE	Picture
<b>FC-2012</b>				 160mm *106mm 273mm*228mm*65mm
			Control 2 doors	
			Readers can connected: 4pcs	
			Memory up 20000 users	
			up to 100,000 Event Buffers	
			Connected to PC by TCP/IP	
			English Software supportable database: Access and SQL	
			With data reports by software	

Model No.:	MOQ	USD	FEATURE	Picture
------------	-----	-----	---------	---------


Model No.:	MOQ	USD	FEATURE	Picture
<b>FC-2014</b>			Control 4 doors	 160mm *106mm  273mm*228mm*65mm
			4 readers can be connected	
			Memory up 20000 users	
			up to 100,000 Event Buffers	
			Connected to PC by TCP/IP	
			English Software supportable database: Access and SQL	
			With data reports by software	


## Feptel Enterprise


MSN: feptel@hotmail.com      Email: telan@feptel.com



Company website: www.feptel.com Tel:86-755-28876034



## Access controller

Model No.:	MOQ	USD	FEATURE	Picture
<b>FC-2010 Access Control</b>			1 Waterproof and weather resistant functions keystroke backlight;	  128mm*82mm*28mm
			2 Change Codes 1 master,500 users & prox cards;	
			3 Door open detection;	
			4 Electric Lock, External Push Switch;	
			5 Magnetic Contacts, Alarm;	
			6 Non volatile Eeprom memory.	
<b>NT111 Network Access Controller&amp; T&amp;A</b>			1 500 users, 5000records;	
			2 RS485Network for 100 units ;	
			Support Wiegand input ;	
			3 Card or card+Pin verification;	
			4 Door monitoring status ready;	
<b>FC-2010R Card</b>			5 Anti-removal function.	
			1 3*4 Matrix keypad;	
			2 Wiegand 26 bit output;	

<b>Card Reader</b>			3 Proximity cards.	
<b>FC-AW1</b>			Metal waterproof access control Support only keypad EM/mifare/HID optional Capacity 2000 users	 120mm*80mm*26mm

Model No.:	MOQ	USD	FEATURE	Picture
<b>NT2 T/A / Access Controller</b>			1 Ergonomic fashion design;	 145mm*95mm*21mm
			2 LCD Chinese/English Menu, Support T/A, access control;	
			3 Online/Offline settings, 15 applications, Holiday setting;	
			4 Data Retention: 10 years(off), Card Interface:EM;	
			5 Offline capacity: 2500 cards, 30000records;	
			6 Transmit: RS485.	

			1 wiegand 26 and RS485 output	 103mm*48mm*21mm
			2 Read Range: 5-15cm, Transmit distance: 100	
			3 waterproof	
<b>R1-EM Card Reader</b>			1 Em card reader	 84mm*84mm*20mm
<b>R1-MF Card Reader</b>			1 mifare card reader	
<b>R2-EM/MF</b>			EM cards readers	
			Mifare cards readers	
<b>Model No.:</b>	<b>MOQ</b>	<b>USD</b>	<b>FEATURE</b>	<b>Picture</b>

Model No.:	MOQ	USD	FEATURE	Picture
FC-2016			2000 fingerprints, 50000 records, User	
			name display, Voice prompt, Dry contact	
			Connect to PC by USB cable/RS485, TCP/IP	
			Wiegand26, Work code, Time zone access	
			control, Bell schedulers, Short message	
			With data reports by software	
				126mm*189mm*35mm
FC-2015 Finger print T/A			1 Time attendance for office desktop use imported Phillip chip ,blue L <sup>™</sup>	
			2 Communication :USB ;	
			3 Sensor : digital;	
			4 Identification time:<=1 sec;	
			5 Register method :fingerprint, ID+password;	
			6 Resolution :500DPI;	
			7 User capacity :512 users;	
			8 Recorder capacity:32000;	
			9 FRR:0.001%;	
			10 FAR:0.00001%;	
			11 Power :220 V ;working voltage :5 V.	












## Feptel Enterprise

MSN: feptle@hotmail.com Email:telan@feptel.com

Company website: www.feptel.com Tel:86-755-28876034

## Accessories

Model No.:	MOQ	USD	FEATURE	Picture
------------	-----	-----	---------	---------

FR125K-W Card Reader Module			1 Card type: EM;	
			2 Output: W26/RS232/ABA.	
Mifare cards			1 Mifare 1K.	
			2 Mifare 4K.	
EM cards			1 Standard shape;	
			2 Non-standard shape.	
FL-01 Locks			1 Electric Bolt.	
FL-02 Locks			1 Electromagnetic Lock.	
FPS-01 Power supply				
RS232/RS485 Converter				
FT-001/4 Exit buttons			1 Exit buttons .	
access video server	<p>Using TCP/IP communication</p> <p>One video server can connect with one camera.</p> <p>Input Signal: One-way</p> <p>Output Mode:TCP/IP</p> <p>Size: 147mm×106mm×42mm</p>			
panel			4-way alarm output	
			Can control: invalid break in alarm, long time unlocking alarm	
			intimidation break in alarm,	
			unlocking linkage output, invalid card swiping alarm,	
			integrated fire control alarm	
			Allow to set anti-intimidation password	
			Can set long time unlocking alarm time: 0-6000 seconds	
			Can set the time delay of each output from 0 to 6000 seconds	

<b>Magnetic Switch</b>			metals shield
			connecting mode: N.C./ N.O.
			rated current : 500(mA), rated voltage : (VDC) 200
			operating distance: more than 35mm, less than90 mm

