



## Shenzhen Wanjiaan Industrial Co.,Ltd

Block 3, KRY-SCN High-Tech Industrial Zone, Huawang Rd

Longhua, Shenzhen, China 518109

http://www.relong.net/en/ www.wanjiaan.com/en/

Tel: 86-755-81486731 Fax: 86-755-28140362

Contact: Jack Zhu (Sales Manager)

Email: jackzhu@wanjiaan.com

## CCTV Camera List

| Photo   | Model          | Resolution                             | Specifications  | Remarks        |
|---|----------------|--|---|----------------|
| <b>H:IR Day/Night Camera</b>  |                |  |   |                |
| <b>1.IR Dome</b>  |                |  |   |                |
|    | <b>H020A</b>   | 420TVL                                 | 1/3" Sony Super HAD CCD   |                |
|   | <b>H020</b>    |  | 3.6mm/6mm IR lens   |                |
|   | <b>H080</b>    | 480TVL                                 | 24 pcs 850nm IR Leds, 15~20m IR Distance  |                |
|   | <b>H020B</b>   | 520TVL                                 | AGC, AWB, BLC, AES  |                |
|   | <b>H050</b>    | 540TVL                                 | Vandal-Resistant Housing<br>DC12V, 500mA  |                |
|   | <b>9020A</b>   | 420TVL                                 | 1/3" Sony Super HAD CCD   |                |
|   | <b>B9020A</b>  |  | Built-in Vari-focal 4~9mm Lens  |                |
|   | <b>H081</b>    | 480TVL                                 | 36 pcs 850nm IR Leds, 25~30m IR Distance  |                |
|   | <b>H081A</b>   | 520TVL                                 | AGC, AWB, BLC, AES  |                |
| <b>9020AH</b>   | 540TVL         | Vandal-Resistant Housing, DC12V, 500mA |   |                |
|  | <b>H026</b>    | 420TVL                                 | 1/3" Sony Super HAD CCD, 4~9mm varifocal<br>42 pcs 850nm IR Leds, 25~30m IR Distance  | Ivory<br>Black |
|   | <b>H086</b>    | 480TVL                                 | Front rotatable 360 degree<br>Ceiling mount and Wall mount  |                |
|   | <b>H056</b>    | 540TVL                                 | Vandal-Resistant Housing<br>AGC, AWB, BLC, AES, DC12V, IP65   |                |
|  | <b>H066</b>    | 650TVL                                 | 1/3" Sony Super HAD CCD, 4~9mm varifocal<br>42 pcs 850nm IR Leds, 25~30m IR Distance<br>Min Lux to 0.1 lux, front rotatable 360 degree<br>OSD, Motion Detection, Privacy Mask, DNR, AGC, AWB, BLC, AES<br>Ceiling and Wall mount, Vandal-Resistant Housing, DC12V, IP65 | Ivory<br>Black |
|  | <b>H022</b>    | 1/3 Sony                               | 420TVL, 3.6mm/6mm IR lens   | Ivory<br>Black |
|   | <b>H023</b>    | 1/4 Sony                               | 36(H022)/24pcs IR Leds, 15~20m IR Distance  |                |
|   | <b>H024</b>    | 1/4 Sharp                              | AGC, AWB, BLC, AES, Plastic housing, DC12V, 500mA   |                |
| <b>2.Weatherproof IR Camera</b>   |                |  |   |                |
|  | <b>H120</b>    | 420, 1/4 Sony                          | 1/3" Sony Super HAD CCD, Built-in Vari-focal 4~9mm Lens   |                |
|   | <b>H121</b>    | 420TVL                                 | 42 pcs 850nm IR Leds, 30~35m IR Distance  |                |
|   | <b>H180</b>    | 480TVL                                 | AGC, AWB, BLC, AES  |                |
|   | <b>3508NVP</b> | 520TVL                                 | 3 Axis concealed cable bracket  |                |
|   | <b>H150</b>    | 540TVL                                 | DC12V, 500mA  |                |
|  | <b>H122A</b>   | 1/4 Sony                               | 1/3" Sony Super HAD CCD   | Ivory<br>Black |
|   | <b>H122</b>    | 420TVL                                 | Built-in Vari-focal 4~9mm Lens  |                |
|   | <b>H181</b>    | 480TVL                                 | 42 pcs 850nm IR Leds, 25~30m IR Distance  |                |
|   | <b>5125NVP</b> | 520TVL                                 | 3 Axis concealed cable bracket  |                |
|   | <b>H151</b>    | 540TVL                                 | AGC, AWB, BLC, AES, DC12V, 500mA  |                |

| Photo   | Model   | Resolution   | Specifications  | Remarks        |
|---|---------|--------------|---|----------------|
|    | H123A   | 1/4Sony      | 1/3" Sony Super HAD CCD   | Ivory<br>Black |
|   | H123    | 420TVL       | Built-in Vari-focal 4~9mm Lens  |                |
|   | H182    | 480TVL       | 48 pcs 850nm IR Leds,30~35m IR Distance   |                |
|   | 5225NVP | 520TVL       | 3 Axis concealed cable bracket  |                |
|   | H152    | 540TVL       | AGC, AWB, BLC, AES,DC12V,500mA  |                |
|    | 5325A   | 1/4Sony      | 1/3" Sony Super HAD CCD   | Ivory<br>Black |
|   | 5325    | 420TVL       | Built-in Vari-focal 4~9mm Lens  |                |
|   | 5325P   | 480TVL       | 42 pcs 850nm IR Leds,25~30m IR Distance   |                |
|   | 5325NVP | 520TVL       | 3 Axis concealed cable bracket  |                |
|   | 5325H   | 540TVL       | AGC, AWB, BLC, AES,DC12V,500mA  |                |
|    | H125    | 420TVL       | 1/3" Sony Super HAD CCD<br>Built-in Vari-focal 4~9mm Lens   |                |
|   | H184    | 480TVL       | 48 pcs 850nm IR Leds,30~40m IR Distance<br>AGC, AWB, BLC, AES,DC12V,700mA   |                |
|   | H154    | 540TVL       | 3 Axis concealed cable bracket  |                |
|    | H126    | 420,8-22mm   | 1/3" Sony Super HAD CCD<br>48 pcs 850nm IR Leds,40~50m IR Distance  |                |
|   | H156    | 540,8-22mm   | 3 Axis concealed cable bracket  |                |
|   | H128    | 420,8-40mm   | AGC, AWB, BLC, AES  |                |
|   | H158    | 540,8-40mm   | DC12V,1000mA  |                |
|  | H127    | 420/600B/W   | 1/3" Sony Super HAD CCD(Color)<br>1/3" Sony Ex-view CCD(B/W)<br>Built-in Vari-focal 8~22mm Lens   |                |
|   | H157    | 540/600B/W   | 48 pcs 850nm IR Leds,50~60m IR Distance<br>AGC, AWB, BLC, AES<br>DC12V,1000mA.Cable invisible bracket   |                |
| <b>3.Fixed lens IR Camera</b>   |         |              |   |                |
|  | H320    | 1/4 Sharp    | 420TVL,3.6mm lens,AGC, AWB, BLC, AES  |                |
|   | H321    | 1/4 Sony     | 14 pcs 850nm IR Leds,15m IR distance.DC12V,500mA  |                |
|  | H322    | 420,1/4Sony  | 1/3" Sony Super HAD CCD   |                |
|   | H324    | 420,1/4Sharp | 3.6mm/6mm/8mm IR lens   |                |
|   | H323    | 420TVL       | 42 pcs 850nm IR Leds,25~30m IR Distance   |                |
|   | H325    | 480TVL       | AGC, AWB, BLC, AES  |                |
|   | 6030H   | 540TVL       | DC12V,1000mA,IP66   |                |
| <b>4.Electronic Sync-focus IR Camera</b>  |         |              |   |                |
|  | H625    | 420TVL       | 1/3" Sony Super HAD CCD,Electronic sync-focus lens5~15mm<br>42 pcs 850nm IR Leds,Vandal-Resistant Housing   | Ivory<br>Black |
|   | H685    | 480TVL       | Cable control,RS485,IP66,Front rotatable 360 degree<br>AGC, AWB, BLC, AES   |                |
|   | H655    | 540TVL       | Ceiling mount and Wall mount,DC12V,DC12V/AC24V option   |                |
|  | H656    | 650TVL       | 1/3" Sony Super HAD CCD,Electronic sync-focus lens5~15mm<br>42 pcs 850nm IR Leds,25~30m IR Distance<br>Min Lux to 0.1 lux,front rotatable 360 degree<br>OSD,Motion Detection,Privacy Mask,DNR<br>AGC, AWB, BLC, AES,Ceiling mount and Wall mount<br>Vandal-Resistant Housing,DC12V,IP65 | Ivory<br>Black |

| Photo   | Model   | Resolution   | Specifications   | Remarks |  |
|---|---------|--------------|--|---------|--|
|    | H626    | 420TVL       | 1/3" Sony Super HAD CCD,Electronic sync-focus lens 4~9mm   |         |  |
|   | H686    | 480TVL       | 48 pcs 850nm IR Leds,25~30m IR Distance  |         |  |
|   | H656    | 540TVL       | Cable control,RS485,IP66,AGC, AWB, BLC, AES<br>3 Axis concealed cable bracket,DC12V,DC12V/AC24V option               |         |  |
|    | H627    | 420,5-15mm   | 1/3" Sony Super HAD CCD,Electronic sync-focus lens   |         |  |
|   | H687    | 480,5-15mm   | AGC, AWB, BLC, AES   |         |  |
|   | H657    | 540,5-15mm   | 48 pcs 850nm IR Leds,40m IR distance   |         |  |
|   | H628    | 420,8-20mm   | Cable control,RS485,IP66   |         |  |
|   | H688    | 480,8-20mm   | 3 Axis concealed cable bracket   |         |  |
|   | H658    | 540,8-20mm   | DC12V,DC12V/AC24V option   |         |  |
| <b>5.Other IR Camera</b>  |         |              |  |         |  |
|    | H728    | 420/600B/W   | 1/3" Sony Super HAD CCD(Color)<br>1/3" Sony Ex-view CCD(B/W),AGC, AWB, BLC, AES                                      |         |  |
|   | H750    | 540/600B/W   | 3.6mm/4mm lens,DC12V,500mA<br>30 pcs 850nm IR Leds,30~40m IR Distance  |         |  |
|    | H729    | 420/600B/W   | 1/3" Sony Super HAD CCD(Color)<br>1/3" Sony Ex-view CCD(B/W),AGC, AWB, BLC, AES                                      |         |  |
|   | H751    | 540/600B/W   | MTV3.6mm IR lens,DC12V,500mA<br>36 pcs 850nm IR Leds,25~30m IR Distance  |         |  |
| <b>K:Box Camera</b>   |         |              |  |         |  |
|  | RL-601H | 540TVL       | 1/3" Sony Super HAD CCD,AGC, AWB, BLC, AES<br>Min Illumination: 0.5Lux/F1.2,Day/Night<br>C/CS lens mount,DC12V,300mA |         |  |
|  | K120    | 420,1/4Sony  | 1/3" Sony Super HAD CCD  |         |  |
|   | K121    | 420,1/4Sharp | Built in 4-9mm lens  |         |  |
|   | K122    | 420TVL       | Min Illumination: 0.5Lux/F1.2,Day/Night  |         |  |
|   | K152    | 540TVL       | AGC, AWB, BLC, AES,DC12V,300mA   |         |  |
|  | K123    | 1/4Sony      | 420TVL,C/CS lens mount   |         |  |
|   | K124    | 1/4Sharp     | Min Illumination: 0.5Lux/F1.2,Day/Night  |         |  |
|   | K125    | 1/3Sony      | AGC, AWB, BLC, AES,DC12V,300mA   |         |  |
| <b>B:Dome Camera</b>  |         |              |  |         |  |
|  | B120    | 420TVL       | 1/3" Sony Super HAD CCD  |         |  |
|   | B121    | 420,1/4Sony  | 3.6mm/8mm lens,AGC, AWB, BLC, AES  |         |  |
|   | B180    | 480TVL       | DC12V,300mA.Min illumination:0.5Lux/F1.2   |         |  |
|  | B127    | 420TVL       | 1/3" Sony Super HAD CCD  |         |  |
|   | B184    | 480TVL       | 4-9mm lens.Min illumination:0.5Lux/F1.2  |         |  |
|   | B154    | 540TVL       | AGC, AWB, BLC, AES,DC12V,300mA   |         |  |
|  | B126    | 420TVL       | 1/3" Sony Super HAD CCD,3.6mm lens.  |         |  |
|   | B183    | 480TVL       | 3 Axis Dome,Min illumination:0.5Lux/F1.2   |         |  |
|   | B153    | 540TVL       | AGC, AWB, BLC, AES,DC12V,300mA   |         |  |
|  | B125    | 420TVL       | 1/3" Sony Super HAD CCD,4-9mm lens.  |         |  |
|   | B182    | 480TVL       | 3 Axis Dome,Min illumination:0.5Lux/F1.2   |         |  |
|   | B152    | 540TVL       | AGC, AWB, BLC, AES,DC12V,300mA   |         |  |
|  | 9010    | 420TVL       | 1/4" Sharp CCD 3.6mm lens  |         |  |
|   | 9015    | 420TVL       | Min illumination:0.5Lux/F1.2   |         |  |
|   | 930C    | 420,1/3Sony  | AGC, AWB, BLC, AES,DC12V,300mA   |         |  |

| Photo   | Model        | Resolution   | Specifications  | Remarks |
|---|--------------|--|---|---------|
|    | <b>B166</b>  | <b>650TVL</b>  | 1/3" Sony Super HAD CCD<br>Min Lux to 0.01,Electronic sync-focus lens 4~9mm<br>Motion Detection,Privacy Mask,DNR<br>Cable control,OSD,RS485,IP65<br>AGC, AWB, BLC, AES,DC12V,DC12V/AC24V option |         |
| <b>T:Zoom Camera</b>  |              |  |   |         |
|    | <b>T221</b>  | Japan lens   | 1/4" Sony Super HAD CCD,480TVL<br>Built-in 3.9~85.8mm 22X Lens,AGC, AWB, BLC, AES,<br>Color:0.5Lux/F1.6,B/W:0.05Lux<br>Auto Color into B/W.DC 12V (+/-10%),500mA                                |         |
|   | <b>T222</b>  | Taiwan lens  |   |         |
|   | <b>T223</b>  | Japan lens   |   |         |
|    | <b>T224</b>  | 480TVL   | 1/4" Sony Super HAD CCD.AGC, AWB, BLC, AES,<br>Built-in 3.9~85.8mm Japan 22Xlens<br>RS485, Pelco-D.Focus speed less than 0.8s.  |         |
|   | <b>T280</b>  | 540TVL   |   |         |
|    | <b>7022</b>  | 480TVL   | 8privacy zones,8mask zones,mirror,color suppress<br>Color:0.5Lux/F1.6,B/W:0.05LuxDay/Night<br>AGC, AWB, BLC, AES,OSD function.DC 12V (+/-10%),300mA   |         |
|   | <b>7022D</b> | 540TVL   |   |         |
|    | <b>T120</b>  | 480TVL   | 1/4" Sony Super HAD CCD.AGC, AWB, BLC, AES,<br>Built-in 3.78~37.8mm 10X Lens Japan lens<br>RS485, Pelco-D.Focus speed less than 0.8s.   |         |
|   | <b>T180</b>  | 540TVL   |   |         |
|   | <b>T121</b>  | 480TVL   | 8privacy zones,8mask zones,mirror,color suppress<br>Color:0.5Lux/F1.6,B/W:0.05LuxDay/Night<br>OSD function.DC 12V (+/-10%),300mA  |         |
|   | <b>T181</b>  | 540TVL   |   |         |
| <b>Q:Speed Dome(PTZ)</b>  |              |  |   |         |
|  | <b>Q180</b>  | 1/4"Sony Super HAD CCD, 480TVL<br>Built-in 3.9~85.8mm Japan 22Xlens<br>8privacy zone,128 preset points,6 tour track,16 auto scan<br>RS485, Pelco-D.Focus speed less than 0.8s.   |   |         |
|  | <b>Q181</b>  | Pan/tilt maximum rotating speed:0.5° -120° /sec<br>0.5Lux/F1.2(color),0.08Lux/F1.2(B/W)<br>AGC, AWB, BLC, AES,Wall mount,AC 24V (+/-10%),2000mA  |   |         |
|  | <b>Q182</b>  | 1/4"Sony Super HAD CCD, 480TVL,3.78~37.8mm Japan 10Xlens<br>8privacy zone,128 preset points,6 tour track,16 auto scan<br>RS485, Pelco-D.Focus speed less than 0.8s.Wall mount<br>Pan/tilt rotating speed:0.5° -120° /sec,AGC, AWB, BLC, AES,<br>0.5Lux/F1.2(color),0.08Lux/F1.2(B/W).DC 12V (+/-10%),500mA |   |         |
|  | <b>Q280</b>  | 1/3"Sony Super HAD CCD, 480TVL,4mm lens<br>RS485, Pelco-D.Focus speed less than 0.8s.Wall mount<br>Pan rotating speed:0.5° -300° /sec.<br>Tilt rotating speed:0.5° -120° /sec,AGC, AWB, BLC, AES,<br>0.5Lux/F1.2(color),0.08Lux/F1.2(B/W).DC 12V (+/-10%),500mA  |   |         |