

8-CH IP-CAM and AHD 1080p Turbo Hybrid DVR



DA-1800T

Features:

Local

- ✓ **8-CH IP-CAM and AHD Turbo 1080p Hybrid DVR** with hexaplex operation - simultaneous record, live, playback, backup, control, & remote access
- ✓ **H.264 High Profile** video compression/decompression with configurable quality
- ✓ **Max record capabilities:**
IP-CAM: 240/200fps@1080p/720p, Analog: 120fps@1080p, 240fps@1080p-lite/720p/960H
- ✓ **Max. 80Mbps incoming bandwidth for IP-CAM**
- ✓ **Smart search** & playback
- ✓ **HDMI * 1, VGA * 1, Main monitor/Call monitor * 1**
- ✓ Audio in * 4 / audio out * 1
- ✓ **eSATA connector for HDD extension**
- ✓ 1 internal SATA HDD
- ✓ Alarm in * 8 / alarm out * 1
- ✓ Ethernet and **USB 3G/4G dongle** support for remote access through I.E. or remote app, e-mail alarm notification, FTP file storage, remote setup and software upgrade

Remote

- ✓ **DVR browser utility**
- ✓ **Free DDNS Server**
- ✓ **Push alarm notification for portable device**
- ✓ Two-way audio capabilities
- ✓ **Audio broadcasting**
- ✓ Dynamic electronics maps for CMS
- ✓ Remote setup, monitoring, backup, alarm notification, & **remote software upgrade**
- ✓ **Remote access through mobile phone/PDA/Mac/Tablet PC with free iPhone/iPad/Android software app**
- ✓ 1 I.E./Firefox/Chrome/App for multiple DVRs
- ✓ Configurable **HTTP/SMTP/FTP/Control/Data** port
- ✓ **Support UPnP, P2P, RTSP and QR code**
- ✓ **MS-Windows/iOS/Android SDK** for the integration with different applications

Specification:

Model		DA-1800T
System	O.S.	Embedded Linux 3.0
	Multiplex	Hexaplex operation - simultaneous record, live, playback, backup, control, & remote access
Video	Format	IP-CAM: ONVIF Profile S; Analog: NTSC/EIA or PAL/CCIR AHD or Analog
	Input	IP-CAM: up to 8-CH 1080p/720p; Analog: up to 8-CH AHD 1080p, BNC, 1Vp-p /75ohm
	Main monitor	HDMI*1 and VGA*1 with resolution up to 1920x1080; BNC*1, 1Vp-p/75ohm
	Call monitor	BNC*1, 1Vp-p/75ohm, shared with Main monitor
	Motion detection	Yes, with configurable detection area & sensitivity
	Privacy mask	Yes
Audio	Input	4 RCA-jack connectors, line-in level (100mV-1Vrms)
	Output	HDMI; 1 RCA-jack connectors, line-out level (up to 1Vrms)
Record	Compression	IP-CAM: H.264; Video: H.264 High Profile ; Audio: ADPCM
	Max frame rate	IP-CAM: 240/200fps@1080p/720p, Analog: 120fps@1080p, 240fps@1080p-lite/720p/960H Up to 80Mbps incoming bandwidth for IP-CAM
	Mode	Manual/Schedule/Alarm/Motion
	Pre-record time	0 - 10 seconds
	Post-record time	0 - 60 minutes
Display	Resolution	HDMI/VGA - up to 1920*1080 ; NTSC - 720*480, PAL - 720*576
	Split windows	1/4/7/9
	Frame rate	Up to 30/25 FPS per display window
	Digital Zoom	X2, X4
Playback	Max frame rate	120fps@1080p, 240fps@1080p-lite/720p/960H
	Search	Smart search, Date/time, Camera, Alarm, Motion
	Operation	Play, Fast Forward, Backward, Pause, Stop, Snapshot, etc.
Storage	HDD	1 set of 3.5" SATA HDD with storage >6TB/HDD; Failure detection & privacy law supported
	HDD Extension	1 optional eSATA connector for up to 5 external HDDs
	Backup	2 USB 2.0 port; Self playback for backup files
Alarm	Input	8 contact or TTL/CMOS signals, polarity selectable
	Output	1 Normally Open or Normally Closed relay outputs
Network	Ethernet	1 RJ-45 10M/100M bps Ethernet connector
	USB 3G/4G dongle	Yes
	Protocol	TCP/IP, HTTP, PPPoE, DHCP, DDNS, FTP, TSP, NTP, RTSP, UPnP, P2P
	Remote	Support Windows 8/7/Vista/XP/2003, N-streaming live view, 1 I.E/Firefox/Chrome/App for unlimited number of DVRs, App for Mac/iPhone/iPad/Android phone and Tablet PC
Control / POS / GPS	Remote Controller	1 remote controller to control up to 4 DVRs; Optional extension cable
	RS-232	1 D-type male connector for PTZ, keyboard, POS, or GPS
	RS-485	2-pin for keyboard and/or PTZ control
Setup	Local	On screen setup via keypad, remote controller, mouse, and/or RS-485 keyboard
	Remote	Setup & upload via Windows/Mac/iPad/Android Tablet application software
Reliability	System recovery	Auto power on after power loss recovery
	Watch Dog Timer	Yes
	Timer	Built-in real time clock
	Security	Multi-level password (4 levels, up to 18 accounts) protection with authentication key for remote access
Weights & Measures	Dimension/ Weight	320(W) x 210(D) x 50(H) 2.0 KG (without HDD)
Power	Source	+12VDC
	Consumption	36W Max.
Operating Temperature		0°C ~ +40°C

AHD 1080p Turbo Hybrid DVR