

FE-500L

FACE CONTROLLER



Face + Mask
Detection



Speed < 1s
(50K 1:N mode)



Multi face verification
(up to 5 people)

FE-500L Specification

CPU	2 core CPU
Memory	1GB RAM, 4G Flash
LCD	5 inch Touch screen
Camera	1MP dual-lens
No. of user Registration	3K user capacitor / 100K Event log
OS	Linux
Function	Face + Mask detection
Power	12V/2A(Max.24W)
Detection	Single/Multi (Up to 3 person)
Range	2-3M
Live detection	Picture, Video can be detected
QR code	YES
Communication	TCP/ WIFI(Optional)
Speed	<1s(1:N, 3k)
RF card	MIFARE
Temperature	-10 - 50°C
Humidity	10% - 90%
Size	165mm×92mm×30mm

99.77%

Recognition Rate

99.77% recognition rate at 1% FAR
99.27% recognition rate at 0.1% FAR

2-3M

Recognition Distance

Long range detection

1 sec

Less than 1 sec

(for 50K user for 1: N authentication)

Live

Photo detection
Video detection
Face + Mask detection

Multi

Possible to authenticate 3-5 people
simultaneously within 1sec

AI

Through AI technology that enables
continuous learning, the recognition
rate is increased by reflecting recent
changes in the user's face.