

NEW IR Vandalproof Dome MBV-3368 Series



IR Vandalproof Dome Camera MBV-3368T & MBV-3368F

- 1/3" SONY Super HAD CCD ,540TVL
- 4-9mm Vari-focal lens(2.8~12mm optional)
- IR distance up to 30M
- 3-Axis bracket inside
- IP66, Vandalproof case
- DC12V

Model	MBV-3368T	MBV-3368F
Signal System	PAL/NTSC	
Image Sensor	1/3" SONY SUPER HAD CCD	
NO. of Effective Pixels	PAL:752(H)X582(V); NTSC:768(H)X494(V)	PAL:500(H)X582(V) NTSC:510(H)X492(V)
Horizontal Resolution	540TVL	420TVL
Lens	4~9mm varifocal lens	
Sensitivity	0.Lux when IR On	
S/N Ratio	More than 52dB	
IR LED	30pc*φ5 IR-LEDs	
IR distance	30M	
Angle of View	30.3°~93.5°	
Iris	Manual	
Gamma Correction	0.45	
Video Output	Composite Video Output(1Vp-p 75ΩTerminated)	
Dimmension	φ54*110	
Operation Temperature	-10°C to +50°C RH95%MAX	
Power Supply	12V DC	
Vandalproof	Yes, IP66	



IR Vandalproof Dome Camera MBV-3368S

- 1/3" SONY Super HAD CCD ,540TVL
- 4-9mm Vari-focal lens(2.8~12mm optional)
- IR distance up to 30M
- OSD menu,D-WDR,2DNR,Privacy Zone,Motion Detection
- 3-Axis bracket inside
- IP66, Vandalproof case
- DC12V

Model	MBV-3368S
Signal System	PAL/NTSC
Image Sensor	1/3" SONY SUPER HAD CCD
NO. of Effective Pixels	PAL:752(H)X582(V); NTSC:768(H)X494(V)
Horizontal Resolution	600TVL
Lens	4~9mm varifocal lens
Sensitivity	0.Lux when IR On
S/N Ratio	More than 52dB
IR LED	30pc*φ5 IR-LEDs
IR distance	30M
Angle of View	30.3°~93.5°
Iris	Manual
Gamma Correction	0.45
Video Output	Composite Video Output(1Vp-p 75ΩTerminated)
Electronic shutter	Auto/Anti-flicker/Manual
DWDR	OFF/ON(0-63 level adjustable)
BLC	HLC/BLC/OFF
White balance	ATW1/ATW2/MANUAL/FIXED
DNR	2D DNR
Day&Night	Auto/B/W/Color/EXT
Motion detection	Off/On(4 areas)
Privacy zones	Off/On(8 areas)
Mirror	Off/On(horizontal mirror)
OSD menu	Chinese/English

AGC	High/Middle/Low/Off
Dimmension	φ54*110
Operation Temperature	-10°C to +50°C RH95%MAX
Power Supply	12V DC
Vandalproof	Yes, IP66