

SH21 HEAT RESIST EXPLOSION PROOF CAMERA HOUSING FOR HIGH TEMPERATURE AREA

FEATURES:

- Ingress protection: IP68
- Wide voltage:AC85~265V/24VAC
- Dual layer of Stainless steel housing
- Strong Tempered window glass
- Two optional cooling way
- Water cooling(bear 0~250°C)
- Inner size:φ130*270mm
- Net weight:4.5kg
- Mounted on wall or pole

APPLICATION:

SH21 series is commercial type of heat resist camera housing, with double layer stainless steel housing, applied for high temperature working place, like metal, steel processing, or furnace monitoring.

PARAMETER

Mechanical

Enclosure material	Dual layer of Stainless steel 304
Ingress protection	IP68
Cable Threaded hole	2 set of G1/2 Glands outlet
Air/water input hole	2*G1/2 gland water input
Net weight	4.5Kg
Overall size	138*158*356mm
Inner install size	φ130*270mm

Environment

Mount	On wall or pole
Operating temperature	0°C~250 °C (circulate water cooling)
Air pressure	80KPa~106KPa
Relative humidity	≤95% (+25°C)

Electrical

Working voltage	AC85~265V, AC24V
-----------------	------------------

TECHNICAL DRAWINGS

