

Your Security, Your Choice

IR Speed Dome
IP Speed Dome

Full HD
1920x1080



69



60



68



66

Mount type	standard: wall mount option: pendant mount
OSD Menu	Chinese/English menu, selectable program, on-screen display
Pan/Tilt	Panning 360° endless rotation, tilting excluding blind zone 92°, manual speed: 0.9°-180°/sec PTZ medium speed : 0.9°-180°/sec
Preset	Support 255 preset position with auto-scan, guarding function that auto-back home point
Auto cruise	6 tours with stay time setting per position
Auto scan	3 auto-scans: left, right, left-right ; 1 limited position scan, supporting left-right limited position and scan at the setting speed
Protocol	Support PELCO-D/P etc, various protocols can be customized
Baud rate	1200, 2400, 4800, 9600 bps
Optional camera	18 ~36 optical zoom
Power supply	DC12V/5A
Infrared distance	>100M

IR Speed Dome (HD IP Speed Dome)



Mount type	wall mount ceiling mount pendant mount
OSD Menu	Chinese/English menu, selectable program, on-screen display
Pan/Tilt	Pan 360° endless rotation, tilt 92°, manual speed:0.9°~180°/sec
Preset	Support 255 preset position with auto-scan, guarding function that auto-back home point
Auto cruise	6 tours with stay time setting per position
Auto scan	3 auto scans: left, right, left-right ; 1 limited position scan
Protocol	PELCO-D/P etc, various protocols can be customization
Baud rate	1200,2400,4800,9600bps
Power supply	DC12V/2A
Infrared distance	>30M



Mount type	standard:wall mount option:pendant mount pendant mount
OSD Menu	Chinese/English menu, selectable program, on-screen display
Pan/Tilt	Pan 360° endless rotation, tilt 92°, manual speed:0.9°~180°/sec
Preset	Support 255 preset position with auto-scan, guarding function that auto-back home point
Auto cruise	6 tours with stay time setting per position
Auto scan	3 auto scans: left, right, left-right ; 1 limited position scan
Protocol	PELCO-D/P etc, various protocols can be customization
Baud rate	1200,2400,4800,9600 bps
Optional camera	18 ~36 optical zoom
Power supply	DC12V / 3A