



TVI FEATURES

- 1/2.9" CMOS image sensor
- 1920x1080P, 1280x720P resolution
- Tribrid system
- 3rd party device compatibility
- Up to 500M HD transmission via coaxial cable
- Day & Night function (ICR)

HT12

- 1/2.9" CMOS Sensor
- 1280x720P (720P, 60/50FPS)
- HD-TVI video output : 1280x720P (720P, 60/50FPS)
- 2DNR

HT22

- 1/2.9" CMOS Sensor
- 1920x1080P (1080P, 30/25FPS)
- HD-TVI video output : 1920x1080P (1080P, 30/25FPS)
- 2DNR

HT21

- 1/2.9" CMOS Sensor
- 1920x1080P (1080P, 30/25FPS)
- HD-TVI video output : 1920x1080P (1080P, 30/25FPS)
- 3DNR
- Real WDR

INDOOR DOME



SK-D300IR

720P : SK-D300R/HT12
 1080P : SK-D300IR/HT21AI
 1080P : SK-D300IR/HT22(AI)
 W/O IR Available
 LED 24pcs(20M) / D&N



SK-DC80IR

720P : SK-DC80IR/HT12
 1080P : SK-DC80IR/HT22
 W/O IR Available
 LED 24pcs(20M) / D&N



SK-V251IR

1080P : SK-V251IR/HT21AI
 W/O IR Available
 LED 24pcs(20M) / D&N / IP68



SK-VC81IR

720P : SK-VC81IR/HT12
 1080P : SK-VC81IR/HT22
 W/O IR Available
 LED 24pcs(20M) / D&N / IP66

VANDAL DOME

PIPE



SK-P563

720P : SK-P563/HT12
 1080P : SK-P563/HT22(AI)
 LED 36pcs(30m) / IP68



SK-P461

1080P : SK-P461/HT21AI
 LED 40pcs(30m) / IP68


BOX



SK-B300

1080P : SK-B300/HT21
 C&CS Mount

HD-TVI DVR (720P)




SK Hybrid 704 (4ch)
SK Hybrid 708 (8ch)
SK Hybrid 716 (16ch)

Key Features

- Up to 4/8/16 cameras with 720p real time preview
- Connectable to network cameras
- All channel 720p real time recording
- HDMI/VGA simultaneous video output

HD-TVI DVR (1080P)



SK Hybrid 104 (4ch)
SK Hybrid 108 (8ch)



SK Hybrid 16 (16ch)

Key Features

- Up to 4/8/16 cameras with 1080p real time preview
- Connectable to network cameras
- All channel 1080p real time recording
- HDMI/VGA simultaneous video output