AKR-70T

1CH Ruggedized Micro DVR

Dimension: 120(W)x56(L)x30(H) mm Resolution: 4CIF/ 2CIF/ CIF


Motion Detection/ Schedule Setup

Light Weight: 150g Pre-Alarm Recording Auto Recording 12/24V Power Support



- CONFIGURATION

FRONT VIEW



REAR VIEW		+		- °C	0
	7 6) <u> </u>	<u> </u>	ž š	ß
Ç			0 0	0 0	0
POWER SEN	SOR IN ALARM	OUT	REMOTE	CONTRO	L
			A		
O DC12- 24V GND DC WDEO IN MIC IN GND WDEO OUT WDEO OUT	AUDIO OUT GND SENSOR IN - GND ALARM OUT -	R+ LED N/A	PWR	0	
00000	00000	0000	0 0		
0	0	REMOTE CON	TROL	0	
	000000		9		
VIDEO IN AUDIO IN	VIDEO OUT	AUDIO O	UT		

VIDEO/ RECORDING			
Compression Format	H.264		
Recording Resolution	4CIF(NTSC:704X480, PAL:704X576)		
	2CIF(NTSC:704X240, PAL:704X288)		
	CIF(NTSC:352X240, PAL:352X288)		
Recording Quality(high)	4CIF:1700Kbps,2CIF:1200Kbps,CIF:1000Kbps		
Recording Frame Rate	PAL: 25, 12, 8, 6, 1 fps		
	NTSC: 30, 15, 10, 6, 3, 1 fps		
Recording Mode	Emergency/ Schedule/ Alarm/ Motion Detection		
Operating Mode	Live/ Playback/ Search		
Storage	Support SD, SDHC (32GB max.)		
Storage File System	FAT16, FAT32		
AUDIO			
Compression Format	16bit PCM, 8KHz		
Input/ Output	1CH. Mono/ 1CH. Mono		
ALARM			
Input/ Output	1/1		
Others			
Searching Method	Time/ Event		
Multi-Port I/O	12pin, Pluggable Terminal Block		
Remote Control Extend Port	6pin, Pluggable Terminal Block		
Power consumption	Approx. 240mA @12V/ 24VDC		





PLAYER (PC VIEWER)