



### Features :

- ✘ With 540TV Lines Resolution.
- ✘ IR Distance Viewing for 30~40M.
- ✘ Various Angle LED Combination.
- ✘ Lens Shading Compensation.
- ✘ Uniform IR Light Distribution for optimum viewing angle.
- ✘ Double Glass: Effectively Reducing the Internal Reflection.
- ✘ Auto Electronic Shutter.



Model	ID-50	ID-52	ID-56	ID-58
Pick up Device	1/3" SONY Super HAD CCD			
Video Pixels	NTSC : 811(H) × 508(V) PAL : 795(H) × 596(V)			
Resolution	540TVL			
Synchronizing System	Internal			
Scanning System	NTSC : 525lines / 60Fields 2 : 1 Interlace PAL : 625lines / 50Fields 2 : 1 Interlace			
S/N Ratio	More than 50dB (AGC OFF)			
Min. Illumination	0.2Lux / F1.8 IR ON / 0Lux	0.2Lux / F1.2 , IR ON / 0Lux		
Video Output	1Vp-p Composite Video / 75Ω			
Auto White Balance	Auto			
Lens Type	Auto Vari-Focal 3.7~14.8mm	CS Lens F1.6 4/6/8/12/16mm		
IR Wavelength	850nm			
IR Led	36pcs 8 Ø LED	30pcs 8 Ø LED		42pcs 8 Ø LED
IR Distance	40M	30M	30M	40M
Power Source / Current	DC12V / 95mA(IR OFF) 400mA(IR ON)			DC12V / 95mA(IR OFF) , 500mA(IR ON)
Operating Temperature	-20°C ~60°C (-4 °F ~140 °F)			
Dimension(W) x (H) x (D) mm	100x95x150	101x95x208	100x90x230	150x110x285
Weight	1000g	795g	805g	880g
Weatherproof	IP68	IP68	IP65	IP66

\* Pick up device can be customization SONY650TVL w/OSD wired controller(WDR) (except ID-50) 、SONY540/420TVL

\* Design and specifications are subject to change without notice.

Welcome to [en.faceid.com.tw](http://en.faceid.com.tw) or call +886-2-2809-2346 for checking the latest details.