

FEATURES

- User Friendly Graphic Interface
- VGA, Composite, S-Video, Loop-Out, SPOT : Video Output at the same time
- Day Light Saving and Free Dynamic DNS IP
- Remote Speed PTZ Control (RS-485)
- Easy Control via USB Mouse, Key Board Controller
- Smart Back-Up with External HDD/DVD-Writer
- Back-Up File Viewer supported
- Outstanding Network Functions for CMS, Network

IMAGE



SPECIFICATIONS

| Description | | DST16480S | | DST16120S | | DST9120S | | DST4120S | | |
|------------------------------|----------------------|--|---|-----------|--------------------------|-------------------------|--------|------------------------|--------|--------|
| Video | Input | Channel | 16ch | | | | 9ch | | 4ch | |
| | | Signal Selection | DIP Switch | | Auto Detection(NTSC/PAL) | | | | | |
| | | Input Level | Composite 1.0Vp-p±10%, 75Ω | | | | | | | |
| | | Video Loss Check | Yes | | | | | | | |
| | Output | Display Output | TV-Out(Composite 1.0Vp-p, 75Ω), VGA-Out(15Pin D-Sub), S-Video | | | | | | | |
| | | Output Level | VGA-Out(15Pin D-Sub), S-Video | | | | | | | |
| Loop-Out | | Loop-Out 16ch / SPOT 1ch | | | | Loop-Out 9ch / SPOT 1ch | | Loop-Out 4ch / No SPOT | | |
| Audio | Input | Channel | 16ch | | 4ch | | | | | |
| | | Compression | G.723 | | ADPCM | | | | | |
| Sensor/Alarm | Input | 16ch | | | | 9ch | | 4ch | | |
| | Output | 4ch | | | | | | | | |
| Display | Rate | NTSC | PAL | NTSC | PAL | NTSC | PAL | NTSC | PAL | |
| | Mode | 480fps | 400fps | 480fps | 400fps | 270fps | 225fps | 120fps | 100fps | |
| Language | Multi-Language | 1,4,9,16 & PIP, POP | | | | | | | | |
| | | English, Spanish, Japanese, Chinese, Polish, Portuguese, etc. | | | | | | | | |
| Recording | Compression | Enhanced MPEG4 | | | | | | | | |
| | Resolution/Rate | NTSC/ PAL | NTSC | PAL | NTSC | PAL | NTSC | PAL | NTSC | PAL |
| | | 360x240 / 360x288 | 480fps | 400fps | 120fps | 100fps | 120fps | 100fps | 120fps | 100fps |
| | | 720x240 / 720x288 | 240fps | 200fps | 60fps | 50fps | 60fps | 50fps | 60fps | 50fps |
| | 720x480 / 720x576 | 120fps | 100fps | 30fps | 25fps | 30fps | 25fps | 30fps | 25fps | |
| | Quality | 4 Level (Best, High, Normal, Basic) | | | | | | | | |
| | Mode | Continuous, Event(Motion, Sensor), Intensive, Schedule, Manual | | | | | | | | |
| Motion Detection Sensitivity | 1-9 | | | | | | | | | |
| Pre Alarm Recoding | Max, 30sec | | | | | | | | | |
| Post Alarm Recoding | Max, 120sec | | | | | | | | | |
| Search | Playback | Mode | Step Forward/Reverse, Play/Pause, Stop, Fast Forward/Reverse | | | | | | | |
| | | Speed | 4 Level (x1, Fast, x2, x3) | | | | | | | |
| | Mode | Time, Event, Direct | | | | | | | | |
| Storage | Internal HDD | Interface Type | S-ATA | | | | | | | |
| | | Max HDD Number | 4 HDD | | | | | | | |
| | Backup Device | CD-RW, DVD-RW, USB Memory | | | | | | | | |
| ETC | Operation System | Embedded Linux | | | | | | | | |
| | PTZ Camera Control | RS-485 | | | | | | | | |
| | Input Method | Front Keypad, Remote controller, USB Mouse | | | | | | | | |
| | KeyBoard Control | External | | | | | | | | |
| | Network | ADSL / Static IP / Dynamic IP(Available Dynamic DNS) | | | | | | | | |
| | Dimension(W x D x H) | 430 x 380 x 95mm | | | | | | 380 x 330 x 68 mm | | |
| | Weight | 5.5KGS | | | | | | 3.5KGS | | |