K-Series 4Ch Surveillance System

Economic to Advanced DVR with IR Cameras and BNC cabling

K540PA / K404PA

Complete 4Ch Surveillance Systems to Satisfy Your Budget and Applications



The Perfect Choice for Security and Surveillance Solution

Panacom is proud to introduce the K-Series 4Ch Surveillance System to

meet the growing demand of the do-it-yourself (DIY) security market. Our offerings are based

on designs with features and performances tried and proven by many of our professional CCTV customers. These are assured to give you the best reliability and the lowest cost-of-ownership.

The K-Series, in addition to the superb operation interface, comes with a fan-less DVR (K540PA, K404PA). The user will benefit from a minimum space requirement, a virtually silent operation, and an easy installation with the included 20-meter video/power cable. The system K404PA can also be enhanced remote and mobile surveillance capability.

We offer three camera options to choose from. These cameras are selected for the customers to meet and balance their budget and performance requirements.

Benefits

- A flexible selection of 2 DVR models: Economic (K540PA) and Network (K404PA).
- Inclusive 20-meter BNC video/power cable for each camera
- Compact size DVR requires minimal space
- Reliable and time-tested features
- Your choice of Day & Night IR cameras.
- Simple, quick, and easy installation and set up.
- Direct from factory with 2-year product warranty.

Features

- Superb picture quality
- Accommodates one 3.5" HDD
- Direct VGA output with up to 1280x1024 resolution
- User-friendly graphic user interface (GUI)
- Easy and flexible operation and control by mouse or IR remote controller
- Video backup to USB pen drive and playback on PC
- Scheduled and motion triggered recording
- Multi-lingual on-screen display (OSD)

With LAN DVR (K404PA):

- Remote viewing via IE, 2.5/3G mobile phone
- Remotely monitor, control, and playback via the internet.



20-meter BNC video/power cable for each camera



Multiple operation control: Mouse / IR controller



Video backup to USB pen drive



Remotely monitor, control, and playback via the internet.



PANACOM TECHNOLOGY CORP.


K-Series 4Ch Surveillance System

Economic to Advanced DVR with IR Cameras and BNC cabling

K540PA / K404PA

Complete Package includes:

- 4ch DVR unit
- 4 Camera Sets
 4 day & night IR cameras,
 each set with: IR Camera x1,
 - Camera Bracketx1, Video/power cable 20m
- Accessories:
 - 1:5 AC-DC Power Adapter and Power Cord for main unit.
- Mouse, CD manual, and IR remote controller.



Order Information

K **X X X** P A - **Y Z**

XXX as the type of DVR:

404 : Network DVR 504 : No Netwrok DVR

Y as the type of cameras A, B or C:

A: Standard CCD IR Camera



B: Type B IR Dome Camera



C: Type C CMOS IR camera



Z as the DVR system P or N :

P: Pal system N: NTSC system

Specification:

	K-series 4ch Surve	illance Syst	em		
Model	K404PA		K540PA		
	DVR Sy	stem			
	Vide	90			
Video Input	BNCx4				
Video Output	VGA-Out x 1				
Display Resolution	NTSC: 640x448,				
Display Nesolation	PAL: 640x544 NTSC: 120fps,				
Display Frame Rate	PAL: 100fps				
Display Mode	Single / Sequence / Quad				
Video Compression	MJPEG				
,	Aud	io			
Audio Input/Output		1	/1		
	Recording/	Playback			
Recording Resolution	Half D1				
Recording Frame Rate	NTSC: 60fps, PAL: 50fps (Auto, Weighted Real-time)				
Recording Mode	Continuous / Schedule / Motion Detection				
Recording Quality	High / Normal / Low				
Playback	Search by Time / Event				
	Netw	ork			
Network Connection	10/100 Ethernet	(RJ-45)		N/A	
Network Protocol	TCP/IP, Static DHCP, PPPoE, D			N/A	
	Storage /	Backup			
Storage Support	One Internal 2.5" SATA HDD				
Backup Device	USB stick				
	Connec	ctors			
USB	USB2.0 Port x 1				
Mouse	Mouse Port (PS/2 Protocol) x 1				
	Security (Camera			
Туре	A (Standard)	B (Optional)		C (Optional)	
Pick-up Element	1/4" SONY CCD	1/4" SONY CCD		CMOS	
Resolution	420I TV lines	420l TV lines		380 TV lines	
Lux Sensitivity	0 LUX (IR ON)	0 LUX (IR ON)		0 LUX (IR ON)	
Number of IR (850nm) LEDs	12 Units	23 Units		12 Units	
IR Project Distance	10~15 Meters	10~15 Meters		5~10 Meters	
Power Consumption	12V DC/400mA	12V DC	/400mA	12V DC/120mA	
	Accesso	ories			
Mouse	Yes (PS/2 Compatible USB Mouse)				
IR Remote Controller	Yes				
Power Supply Unit	Input: AC100~240V, 50/60Hz				
FUWEL SUDDIV UNIT	Output: 1+4 DC12V, 5A				

We gladly accept OEM/Private Label Orders.

