



## 3X Optical Mini PTZ Dome ANC-3420MB

IP66  
Vandal Proof  
SONY sensor  
Auto tracking  
ONVIF2.4 / Profiles

### Features :

Support 2 way audio  
Free bundled 64CH recording software  
Superior video effect in dark environment  
Complied with IP66 for outdoor installation  
Built - in Motion Detection & Email Notification  
Built - in Micro SD Card slot for easy storing and playback image/video  
Support cutting edge feature of auto tracking function for moving objects  
Outdoor PTZ type in palm-size with unique interior IR Led and full function of I/O interface  
6 high power leds with mechanical ICR and auto light sensor for day and night monitoring

### Specfication

3X optical zoom , 4X digital zoom  
Support Auto focus / Smart focus / Step focus  
Up to 30 fps at 1920 x 1080 of video resolution  
Built - in Samba function for storing image/video at local area network directly  
Support advanced setting of WDR, 3D NR, Auto Iris, Low lux mode, Exposure control

### Connectivity

Support OS: Microsoft Windows XP/Win7/Win8/Win10  
Support H.264 / MPEG4 / MJPEG multi-codec and multi-streaming  
Support easy installation with NAT transversal DDNS server for port setting free  
Support connectivity with iPhone, smart phones and all browsers including IE, Firefox, Chrome, Safari and Opera



### Setting

Support OS: Microsoft Windows XP/Win7/Win8/Win10  
Browser - Internet Explorer 8.x or above, Firefox, Chrome, Safari and Opera



### Package

Camera, Power Adapter, Ceiling mount bracket, Installation Software & Manual on CD, Quick Installation



Power Adapter



Software CD



Quick Guide



bracket



Screws

## Specifications

<b>System</b>	RAM : 4GB DDR ROM : 16MB flash ROM
<b>Camera specification</b>	1/2.8 Sony CMOS sensor IMX322 Resolution:1920x1080
<b>IR Led</b>	Auto/Manual mode, above 20 meters visible Spectral band width 42nm, Peak emission wavelength 850nm Daylight sensor, angle +/-65, wave length 400~700nm
<b>Lens</b>	3X optical zoom lens, auto iris, auto focus f = 2.8mm ~ 12mm, F1.8 Fov(D), 136° ~ 39°
<b>Protocol</b>	TCP/IP, HTTP, SMTP, FTP, DDNS, UPnP, Telnet, NTP, PPPoE, DNS, DHCP and RTSP
<b>Video Resolution</b>	Up to 30 frames at 1920X1080, 1280x1024, 1280x800, 640x480, 320x240 and 176x144
<b>Algorithm supported</b>	H.264/MPEG4/MJPEG multi-codec for streaming video JPEG for still image
<b>Audio</b>	G.711/AMR/AAC Omni-directional Microphone Support 2 way audio
<b>Physical</b>	10 baseT or 100 baseT Fast Ethernet auto negotiation
<b>I/O Interface</b>	RJ-45, DI, DO, Mic. In, Audio out, DC Power, Micro SD Slot(inside camera)
<b>Power</b>	Input: 100-240VAC, 50/60Hz, 0.7A Output: 12VDC, 1.5A Consumption: Max 10 W Support 802.3af compliant Power over Ethernet
<b>Pan/Tilt angle</b>	Support auto tracking function Support multi - direction movement Pan : 250° Tilt : 75°
<b>EMI &amp; Safety</b>	CE, FCC
<b>Dimension</b>	Height : 72.5mm, Diameter : 93.8mm(excluding 3 mounts)
<b>Operating Environment</b>	Temperature : -5 ~ 50°C Humidity : 85% RH
<b>Weight</b>	NET. 500g

※ Products specifications and design subject to change without notice ※