



Powerful Surveillance Secure Your Life
The Home Security Solutions

PT Type H.264

Wireless IP Camera



IP surveillance

ICS2330



Key Features

- IEEE 802.11b/g/n Wireless Network
- Resolution up to 1280 x 1024 pixels
- Day/Night Function – Infrared LEDs with 5m effective range
- Pan/Tilt/Digital Zoom
- 3 x digital zoom
- USB port for local storage device
- Digital Input / Output (GPIO) ports to an alarm system
- Quick Universal Plug and Play installation
- Remote Monitoring from Mobile phone

Product Overview

The device is PT Type H.264 Wired/Wireless IP Camera with 1.3 Mega-pixel sensor. With high performance H.264 video compression, the file size of video stream is extremely reduced, as to optimize the network bandwidth efficiency. It has full Pan/Tilt function and 3X digital zoom feature for a larger space monitoring. The built-in USB port provides a convenient and portable storage option for local storage of event and schedule recording, especially network disconnected.


IP Camera Application



<http://www.ipux.net>

Address: 8F, No.356, Neihu Road Sec. 1, Neihu District, Taipei, Taiwan
Phone:886-2-2656-0242 Fax:886-2-2656-2966

©2012 IPUX. All other company names and products are trademarks or registered trademarks of their respective companies. We reserve the right to introduce modifications without notice.



ICS2330

Camera

Model Number ICS2330 - 1.3Mega/ Pantilt/ IR LED/ Wireless

Hardware System Network Processor: ARM9 Base
Flash: 8M
RAM: 64M

Image Sensor Sensor Type : 1/4" CMOS Megapixel Sensor
Sensor Resolution : 1280 x 1024 pixel
Minimum Illumination : 0 Lux IR LED on

Lens Focal Length: Board Lens 4.0mm, F2.8
Horizontal/ Vertical/ Diagonal angle:
58.1°/ 44.8°/ 60°

Video

Video Image Compression H.264 / MPEG4 / MJPEG

Video Setting Auto Exposure Control/ Auto White Balance/
Auto Gain Control

Image Resolution and Frame Rate SXGA (1280 x 1024) : 15 fps
720p (1280 x 720) : 15 fps
VGA (640 x 480) : 30 fps
QVGA (320 x 240) : 30 fps
QQVGA (160 x 120) : 30 fps

Multi-Profile H.264@SXGA/720p/VGA/QVGA/QQVGA and
MPEG4@VGA/QVGA/QQVGA and
MJPEG@SXGA/VGA/QVGA/QQVGA

Pan-Tilt Pan: +165~-165 degree
Tilt: +90~-15 degree
Auto Patrol preset positions: 8 positions
Pan 330° side-to-side and tilt 105° up-and-down from any Internet connection

Audio

Audio In Internal Omni-directional Microphone
Sensitivity: more than -42dB +/- 3dB

Audio Out Line Level Out ;1 Vrms ;
3.5mm Phone Jack; Mono

Audio S/N Ratio More than 60dB

Network

Network 10/100 Mbps Ethernet, RJ-45
802.11b/g/n WLAN
WPS button
Protocols:
TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS,
SMTPs, FTP, HTTP, Samba, PPPoE, UPnP,
Bonjour, RTP, RTSP and RTCP

Distributed by:

General

Digital Zoom 1X, 2X, 3X

Security Multi-level user access with password protection
WEP 64/128bit , WPA(2)-PSK(AES/TKIP)

LED and Button Power
Link/Act.
Reset Button

USB Port Yes, USB 2.0

Power Power Input: DC 12V
Power consumption: Max. 10W

Environment Operating Environments :
Temperature: 0 ~ 45 °C
Humidity: 20% ~ 85% RH

Dimension 149.1mm (D) x 110.7 mm (W) x 100.9mm (H)

Weight 345g

Certification FCC / CE class B

External View



Package Contents

Contents Network camera
Multi-language Quick Installation Guide
CD-ROM (Utility and User's Guide)
Cat.5 Ethernet cable (1.8m / 5.9ft)
Power adapter (12VDC,1.5A)
Antenna

IPUX

<http://www.ipux.net>

Address: 8F, No.356, Neihu Road Sec. 1, Neihu District, Taipei, Taiwan
Phone:886-2-2656-0242 Fax:886-2-2656-2966

©2012 IPUX. All other company names and products are trademarks or registered trademarks of their respective companies. We reserve the right to introduce modifications without notice.