

EYEBALL DOME CAMERA

WEATHERPROOF IR CAMERA



CE FCC

- FEATURE**
- ▶ Ultra High Resolution (600TVL)
  - ▶ Super Sensitivity
  - ▶ 2D-DNR (Digital Noise Reduction)
  - ▶ D-WDR (Wide Dynamic Range)
  - ▶ Intelligent IR Control (Smart IR)
  - ▶ 2.8-11mm DC AIVF Lens Available
  - ▶ Weatherproof Vandal Resistant
  - ▶ 3-Axis Gimbal Structure
  - ▶ 36 IR LED Built-In
  - ▶ True D&N ICR (Optional)
  - ▶ Dimension : 120(W) x 99(H) x 120(L) mm



CE FCC



Built-In OSD Control Cable (IP66)

- FEATURE**
- ▶ Ultra High Resolution (600TVL)
  - ▶ Super Sensitivity
  - ▶ 2D-DNR (Digital Noise Reduction)
  - ▶ D-WDR (Wide Dynamic Range)
  - ▶ Intelligent IR Control (Smart IR)
  - ▶ 6mm Lens Available
  - ▶ 3-Axis Cable-Through Bracket
  - ▶ 60 IR LED Built-In
  - ▶ True D&N ICR (Optional)
  - ▶ Dimension : 90(W) x 82(H) x 147(L) mm (Excluding Bracket)

SPECIFICATION

ITEM	NTSC	PAL
TDAI Pixels	874(H) x 238(V)	792(H) x 238(V)
Effective Pixels	768(H) x 424(V)	752(H) x 424(V)
Sensor	1/3 inch Interline Transfer CCD (ICX 639 / 639 BK)	
Scanning System	2:1 Interlaces	2:1 Interlaces
Resolution	More than 600 TV Lines	
Video Output	1.0Vp Composite signal (75ohm)	
S/N (V signal)	52dB (AEC OFF/Weight ON)	
Illumination	OFF / LOW / MIDDLE / HIGH Selectable	
Gain Control	0.001Lux	
White Balance	ATW2300K-4500K / ATW22.000K-11.000K / MANUAL	
Electronic Shutter speed	1/ 50 sec - 1/120,000 sec	
O.S.D	Built-in	
D.IXDR	OFF / ON	
20.00MG (Digital Noise Reduction)	OFF / ON / Level Selectable -x25	
DATA Selection	AUTO / ON / Level Selectable -x25	
Smart IR Control	OFF / ON / Level Selectable -x25	
Backlight	OFF / B.C / H.C	
Privacy Masking	0.2mm	
Sharpness	OFF / ON	
L.S. (Lens Shading Control)	OFF / ON / Level Selectable -x25	

FUNCTION



520TVL



600TVL



DNR OFF



DNR ON



Smart IR OFF



Smart IR ON



WDR OFF



WDR ON



HSBLC OFF



HSBLC ON