

HD-SDI surveillance solutions

SINCE 1991
SAMBO
 SAMBO HITECH CO.,LTD.



FEATURES

- 1/3" 2.1M Panasonic CMOS
- FULL HD Resolution : 1100TVL
- 1920x1080 pixel/30fps, 1280x720 pixel/60fps
- Enhanced **WDR** performance
- 3D-DNR / SENS-UP / D.ZOOM
- Motion Dection / Privacy Masking / DEFOG**
- Built-in OSD key (Inernal adjustment)
- Video Out : HD-SDI & Analogue (CVBS)
- RS485/ PELCO-D / PELICO-P
- Power Source : DC12V (6.5V~28V)



Enhanced WDR Funcion



Enhanced 3D-DNR reduces noise much better han ever



HD-SDI offers digial Zoom and PIP function.



Defog function enables clearer images against fog or mst or any islow contrast picture



Dynamic Digital Zoom up to x64 and PIP

4/7/16 ch HD-SDI DVR with Real-time

www.sbcctv.co.kr



- 16ch HD-SDI Video Input (720p or 1080p)
- 1080p Real-time (Max 30fps per channel) Recording & Playback
- HDMI & VGA Output Full HD (Max. 1,920x1,080p)
- 8ch Audio In & 1ch Audio out
- Dual Stream : Optimize network transfer speed
- 4 HDD (Up to max 12TB) -3TBx4
- CMS up to 64channel Display in a Tab (Up to max 4 Tab)



- 4 / 7ch HD-SDI Video Input (720p or 1080p)
- HD Real-time (Max 30fps per channel) Recording & Playback
- HDMI & VGA Output Full HD (Max. 1,920x1,080p)
- 4ch Audio In & 1ch Audio out
- Dual Stream: Optimize network transfer speed
- 2 HDD (Up to max 6TB) -3TBx2
- CMS Up to 64channel Display in a Tab (Up to max 4 Tab)
- Support Web viewing through IE



ISO14001 ISO9001
 CE CB FC RoHS FDA C